

STATUS OF THESIS

Title of thesis

**Slope Deformation Monitoring Using Reflector-less
Total Station**

I MOHD ASRI BIN HJ. ZAHID@MAMAT

hereby allow my thesis to be placed at the Information Resource Center (IRC) of Universiti Teknologi PETRONAS (UTP) with the following conditions:

1. The thesis becomes the property of UTP
2. The IRC of UTP may make copies of the thesis for academic purposes only
3. This thesis is classified as

Confidential

Non-confidential

If this thesis is confidential, please state the reason:

The content of the thesis will remain confidential for _____ years.

Remarks on disclosure:

Endorsed by

Signature of Author

Permanent Address:
Dept. of Civil Engineering
Ungku Omar Polytechnic
Jln. Raja Musa Mahadi
31400 Ipoh, Perak

Date: _____

Signature of Supervisor

Permanent Address:
Civil Engineering Department
Universiti Teknologi PETRONAS
Bandar Seri Iskandar, Perak
Malaysia

Date: _____

UNIVERSITI TEKNOLOGI PETRONAS
SLOPE DEFORMATION MONITORING USING REFLECTOR-LESS
TOTAL STATION
by
MOHD ASRI BIN HJ. ZAHID@MAMAT

The undersigned certify that they have read, and recommend to The Postgraduate Studies Programme for acceptance this thesis for the fulfillment of the requirements for the degree of Master of Science in Civil Engineering.

Signature: _____

Main Supervisor: _____

Date: _____

Signature: _____

Head of Department: _____

Date: _____

UNIVERSITI TEKNOLOGI PETRONAS

SLOPE DEFORMATION MONITORING USING REFLECTOR-LESS
TOTAL STATION

by

MOHD ASRI BIN HJ. ZAHID@MAMAT

A Thesis
Submitted to the Postgraduate Studies Programme
as a Requirement for the Degree of

MASTER OF SCIENCE
CIVIL ENGINEERING
UNIVERSITI TEKNOLOGI PETRONAS
BANDAR SRI ISKANDAR
PERAK

JANUARY, 2010

DECLARATION OF THESIS

Title of thesis

Slope Deformation Monitoring Using Reflector-less Total Station

I **MOHD ASRI BIN HJ. ZAHID@MAMAT**

hereby declare at the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UTP or other institutions.

Witnessed by

Signature of Author

Signature of Supervisor

Permanent Address:

Dept. of Civil Engineering
Ungku Omar Polytechnic
Jln. Raja Musa Mahadi
31400 Ipoh, Perak

Name of Supervisor:

Date: _____

Date: _____

ACKNOWLEDGEMENT

First and foremost, I am humbly grateful to ALLAH the almighty, that by His grace and blessings I have been able to complete this thesis. I am very grateful to my parents, who have taught me the meaning of struggle in this life. No words of thanks can adequately express the depth of my appreciation and love to my lovely wife Noor Alina Hj. Mansor and my five beautiful children Ameira, Atiera, Aisyah, Awatif and Muhammad Aqif for their true love and support. Their love has given me the courage and becomes the power in my life, and always makes my life more meaningful.

In preparing this thesis, I have been in contact with many people, researchers, academicians, and practitioners who have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main thesis supervisor, Dr. Abd. Nasir Matori. I cannot express the extent to which his support and understanding has allowed me to reach the end of this journey. His encouragement, support, understanding and, above all, his prompt, constructive and greatly appreciated criticism and feedback, were invaluable to the research, writing and completion of this study. Thank you.

Thanks and gratitude must be given to Mr. Ismail project manager of MTD construction group, Mr. Noor Azman Embi from Jurukur Esa, Mr. Zulkifli Rais from Jurukur Perunding services, and Jabatan Kerja Raya for allowing me to access and providing the data for my research. Thanks are extended for the staff of Post Graduate Studies Office especially Mrs. Kamaliah and Mr. Hizwan for their invaluable help and cooperation.

Last but not least, I wish to thank my fellow friends Mrs. Yeni, Mr. Dedi, Mr. Basith, Mr. Joko and his family, Mr. Bambang and his family who have supported and comforted me through the good and bad times; they have given me a lot of fun and unforgettable moments.

Slope Deformation Monitoring Using Reflector-less Total Station

Abstract

Continuous deformation monitoring of slope along the roads and highways in Malaysia is one of the most effective method of early landslide detection, which could contribute to avoiding or reducing the risk of landslide. There are many factors that influence the success of the monitoring system such as accuracy of the instruments, existing information, frequency of slope failure in a particular area, size of potential hazard area and the involvement of people in that project. To overcome the above problems Reflector-less Total Station method is introduced as an alternative method. This method is able to reduce the usage of reflectors, thus more survey points can be covered. It is also more economical since not only the costs for the prisms are saved, but high installation expenses can also be reduced. Additionally it can lower the risk to the people involved in measuring slope deformation in areas that are dangerous and difficult to access.

This research focuses on the potential of using reflector-less Total Station for slope deformation monitoring. In order to check the performance and reliability of the reflector-less Total Station, periodical calibration of the instrument is necessary. The instrument with its related reflectors is calibrated to verify its constant and scaling errors, which is often accomplished by calculation from a series of measurements on a calibration baseline. A parametric least squares formula was used to obtain the constant and scaling correction calculations based on the series of distances on six sub-baselines. The calibration was performed at Jabatan Ukur dan Pemetaan Malaysia (JUPEM) permanent calibration benchmarks at Batu Gajah, Perak Malaysia. The result shows that the values of the constant and scaling corrections for the prism and the various targets are less than the values of the instrument specification, which indicate that the reflector-less Total Station is functioning well. Data on slope deformation monitoring were collected for the three epochs within a six months gap of each other and were carried out independently in the study area located at chainage 23+800 at Simpang Pulai - Cameron Highland highway. To prove that the movement is significant, statistical test has been

adopted in this study using t-student distribution. The test results show that there is a significant movement in the study area, whereby there has been a maximum of 0.09 m in the northing, 0.08 m in the easting and 0.012 m in the elevation in some of the points during the 18 months observation period.

Keywords deformation1, monitoring2, calibration3, reflector-less4, total station5

Pengawasan Deformasi Cerun menggunakan Alat Stesen Penuh Tanpa Pemantul

Abstrak

Pengawasan berterusan pergerakan cerun di sepanjang jalan dan lebuhraya-lebuhraya di Malaysia adalah salah satu cara yang paling efektif untuk mengesan tanda awal kejadian tanah runtuhan, bagi mengelakkan atau mengurangkan risiko tanah runtuhan. Walau bagaimana pun terdapat banyak faktor yang mempengaruhi kejayaan sesuatu sistem pengawasan, seperti ketepatan peralatan, maklumat yang sedia ada, kekerapan berlaku pergerakan cerun dalam sesebuah kawasan tertentu, keluasan kawasan berisiko tinggi dan penglibatan tenaga manusia didalam projek tersebut. Untuk mengatasi masalah ini, penggunaan alat stesen penuh tanpa prisma telah diperkenalkan sebagai satu kaedah alternatif. Kaedah ini dapat mengurangkan penggunaan alat prisma, dari itu lebih banyak titik-titik pengukuran boleh diambil. Ia juga lebih ekonomikal kerana bukan sahaja kos alat tersebut boleh dijimatkan malahan kos pemasangan yang tinggi juga dapat dikurangkan. Disamping itu, penggunaan peralatan ini juga dapat mengurangkan risiko kepada pekerja yang menjalankan pengawasan cerun di kawasan merbahaya dan juga yang sukar dimasuki.

Penyelidikan ini memberi tumpuan kepada potensi penggunaan alat stesen penuh tanpa prisma untuk pengawasan cerun. Bagi tujuan memeriksa prestasi dan kebolehpercayaan alat stesen penuh tanpa prisma, ujian penentukan berkala alat tersebut adalah perlu. Alat tersebut berserta pemantul berkaitan ditentukur untuk menentukan pemalar dan ralat penskalaan yang kebiasaannya boleh dilakukan menggunakan pengiraan berdasarkan beberapa siri pengukuran di garis tapak penentukur. Formula kuasa dua terkecil parametrik telah digunakan untuk mendapatkan pemalar dan pengiraan pembetulan penskalaan berdasarkan beberapa siri jarak pada enam garis tapak kecil. Penentukan ini telah dijalankan di tapak penentukan piawai Jabatan Ukur dan Pemetaan Malaysia (JUPEM) yang terletak di Batu Gajah, Perak Malaysia. Keputusan menunjukkan bahawa nilai pemalar dan pembetulan penskalaan untuk prisma dan beberapa sasaran adalah lebih rendah dari nilai spesifikasi alat tersebut, yang menunjukkan bahawa alat stesen penuh tanpa prisma itu berfungsi dengan baik. Data

pengawasan cerun telah dicerap bagi tiga epok pada sela masa enam bulan di antara satu sama lain dan telah dijalankan secara berasingan di kawasan kajian yang terletak di rantaian 23+800 lebuh raya Simpang Pulai–Cameron Highland. Bagi membuktikan bahawa pergerakan adalah signifikan, ujian statistikal telah digunakan dalam kajian ini menggunakan taburan t. Analisis kajian telah menunjukkan berlaku anjakan tanah yang ketara di tapak kajian, dimana terdapat beberapa titik yang telah berganjak sebanyak 0.09 m bagi komponen utaraan, 0.08 m bagi komponen timuran dan sebanyak 0.012 m bagi komponen pugak bagi tempoh cerapan selama 18 bulan.

Kata kunci deformasi¹, pengawasan², kalibrasi³, tanpa pemantul⁴, stesen penuh⁵

In compliance with the terms of the Copyright Act 1987 and the IP Policy of the university, the copyright of this thesis has been reassigned by the author to the legal entity of the university,

Institute of Technology PETRONAS Sdn Bhd.

Due acknowledgement shall always be made of the use of any material contained in, or derived from, this thesis.

© Candidate Name, 2009
Institute of Technology PETRONAS Sdn Bhd
All right reserved

TABLE OF CONTENTS

	PAGE
STATUS OF THESIS.....	i
APPROVAL PAGE.....	ii
TITLE PAGE	iii
DECLARATION.....	iv
DEDICATION	v
ACKNOWLEDGEMENT	iv
ABSTRACT	x
COPYRIGHT PAGE.....	xii
LIST OF TABLES	xiii
LIST OF FIGURES.....	xv

Chapter

1. INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement.....	3
1.4 Scope of the Research.....	4
1.5 Outlines of Thesis.....	5
2. LITERATURE REVIEW	6
2.1 Introduction.....	6
2.2 Slope Failure in Malaysia	6
2.3 About the Study Area	10
2.4 Monitoring of Slope Failures	12
2.5 Deformation Survey	13
2.6 Method of Deformation Analysis.....	14
2.7 Concepts and Procedures of Deformation Detection	14
2.8 Types of Instruments and Techniques for Monitoring Deformation ..	15
2.8.1 Monitoring by Instruments Techniques	16
2.8.2 Monitoring by Observational Techniques.....	17
2.8.2.1 Global Positioning System (GPS)	17
2.8.2.2 Remote Sensing Method	18
2.8.2.3 Terrestrial Survey Method.....	19

2.9	New Generation of Total Station (TS) Instruments	20
2.10	Types of Reflector-Less Total Station	22
2.11	Theory of Errors Propagation in Total Station Observations	23
2.11.1	Error Propagations in Distance Observation	23
2.11.1.1	Constant Error for Different Reflecting Surface Materials	27
2.11.2	Error Propagations in Angle Observation	29
2.11.2.1	Pointing and Reading Errors with Total Stations..	31
2.11.2.2	Target Centering Errors.....	31
2.11.2.3	Instruments Centering Errors	34
2.11.3	Error Propagations in Elevation Observation	37
2.11.4	Error Propagations in Traverse survey.....	40
2.12	Data Screening	42
2.13	Standard Deviation of Displacements	44
2.14	Analysis of Displacements	46
2.15	Summary of the Literature Review	48
3.	METHODOLOGY	50
3.1	Introduction	50
3.2	Description of Study Area	51
3.3	Reflector-less Total Station Calibration.....	52
3.3.1	Apparatus	52
3.3.1.1	Total Station	53
3.3.1.2	Reflector Targets	54
3.3.1.3	Calibration Pillars	55
3.4	Total Station Calibration	56
3.5	Data Processing	57
3.6	Zero Error Estimation	59
3.6.1	Calibration of Distance Measurement Tool in the TS.....	61
3.7	Control Points	62
3.8	Reflector-less Monitoring Points	63
3.9	Data Collection	64
3.10	Data Reductions	66
3.11	Observation Errors	67
3.12	Displacement Test	68
3.13	Quality Measurement of Deformation Monitoring Points	68
3.14	Experimental Work Flow	69
4.	RESULTS AND DISCUSSION	73
4.1	Introduction	73
4.2	Total Station Calibration	73
4.2.1	Results of Zero Error Estimation	74
4.2.2	TS Calibration Factors for Different Types of Target	77
4.3	Datum Verifications	79
4.3.1	Baselines by GPS Observation	79
4.3.2	Datum Verifications by Total Station Observation	81

4.4	Errors Propagation	82
4.4.1	Errors Sources in Horizontal Angles	82
4.4.2	Errors Sources in Electronic Distance Observations	84
4.4.3	Errors Sources in Trigonometric Leveling	85
4.4.4	Estimated Error in Latitude and Departure	86
4.5	Magnitude of Movements	87
4.6	Displacement Test	89
4.7	T-Test with Standard Prism	94
5.	CONCLUSION AND RECOMMENDATIONS.....	97
5.1	Conclusions	97
5.2	Recommendations and Future Works.....	100
	REFERENCES	102
 APPENDICES		
A.	Specification of Topcon GPT-3007 N/LN Reflector-less TS.....	108
B.	F Distributions Critical Values	111
C.	T Distributions Critical Values	113
D.	Mean of Observation Data of Control Points	114
E.	Coordinates Difference between Epochs with Standard Prism TS	115
F.	Coordinates Difference between Epochs with Reflector-less TS	118
G.	Standard Deviation of Latitude and Departure	121
H.	Letter from JKR	124
I.	Raw Data of Calibration Using Reflector-less Total Station	126
J.	Raw Data of Monitoring Target Points Measured Using Reflector-less Total Station	140
K.	Errors Sources in Horizontal Angles	146
L.	Errors Sources in Horizontal Distance	149

LIST OF TABLES

Table	Page
2.1 Number of catastrophic landslides in Malaysian	8
2.2 Overview of methods used in measuring surface displacement	12
And their precision	
2.3 Accuracy requirements for structure target point	15
2.4 Centering errors for different types of centering equipments	32
3.1 The standard value between pillars provided by JUPEM	56
4.1 F-computed for global test	74
4.2 Zero error and standard deviation for various targets	74
4.3 T-computed from significant test for zero error correction	77
4.4 Adjusted sub baseline for various material targets	77
4.5 TS constant value and scaling factor for various type of target	78
4.6 T-computed for significant test of Total Station calibration	78
4.7 GPS Coordinates	80
4.8 Comparison result between results of GPS vs. MTD	80
4.9 Datum verification between MTD on 12/02/03 and epoch 1 on..... 07/02/08	81
4.10 Datum verification between epoch 1 on 07/02/08 and epoch 2 on	81
07/07/08	
4.11 Datum verification between epoch 2 on 07/07/08 and epoch 3 on	82
07/12/08	
4.12 Standard deviation of elevation	86
4.13 The N, E and H coordinate in meters of the 20 monitoring targets	87
Object	
4.14 Horizontal and elevation displacements and T-computed between	91
Epoch 1 and epoch 2	

4.15	Horizontal and elevation displacements and T-computed between Epoch 2 and epoch 3	92
4.16	Horizontal and elevation displacements and T-computed between Epoch 1 and epoch 3	93
4.17	T-computed and coordinates difference between standard prisms TS and reflector-less TS between Epoch 1 and Epoch 2	94
4.18	T-computed and coordinates difference between standard prisms TS and reflector-less TS between Epoch 2 and Epoch 3	95
4.19	T-computed and coordinates difference between standard prisms TS and reflector-less TS between Epoch 1 and Epoch 3	96

LIST OF FIGURES

Figure	Page
2.1 Number of Landslides Events in Malaysia (1961-2007).....	7
2.2 Frequencies of Slopes Failures at Cameron Highland	9
2.3 Overview of study area location, captured by aerial photograph	10
2.4 Sequences of land slide 2001 - 2003 at CH 23+800	11
2.5 Object points representing the object under investigation are	13
connected by Geodetic measurements	
2.6 Geotechnical methods and special instruments	16
2.7 Real time monitoring system	20
2.8 Phase shift EDM (Distance = $\frac{1}{2}$ (m x λ +d).....	22
2.9 Timed pulse EDM (Range = Time x speed of light/2 = $\frac{1}{2}$.c. Δt).....	23
2.10 Principles of Electronic Distance Measurement (EDM)	24
2.11 Three peg tests	26
2.12 Standard pillar for EDM baseline	26
2.13 The Kodak neutral test card	27
2.14 Direct target to various surfaces	28
2.15 Constant Errors of various reflecting materials	29
2.16 Simulation of virtual survey scenario	30
2.17 Reference axes of total station	30
2.18 Possible target locations	32
2.19 Error in an angle due to target centering error	33
2.20 Error in an angle due in instrument centering	34

2.21	Analysis of instrument centering error	35
2.22	Instrument centering error at a station	36
2.23	Determination of elevation difference by trigonometric leveling	38
2.24	Curvature and refraction (CR)	39
2.25	Latitude and departure	41
2.26	Latitude and departure errors on distance (a) and azimuth (b).....	41
2.27	The “Rule of Thumb” of three standard deviations (SD)	43
2.28	Calculation of displacement	44
2.29	Calculation of horizontal displacement.....	45
3.1	Location map	51
3.2	Topcon GPT3007 N/LN Reflector-less TS used in this research.....	53
3.3	Various material target reflector used in this research.....	54
3.4	A standard single prism used in this research	55
3.5	Pillars calibration used in this research.....	55
3.6	Illustration of the calibration scenario; calibration pillars (middle), standard sub baselines (top), and all measured distances (bottom)	57
3.7	Control point established by MTD	62
3.8	Checking control point using GPS.....	63
3.9	Monitoring points	64
3.10	New reference target	64
3.11	Setting the prism/non-prism constant value	64
3.12	Station No.44.....	65
3.13	Control point station	65
3.14	Set-up for the field work	66

3.15	Experimental work flow of this research.....	72
4.1	Distance differences base on colors	76
4.2	Distance differences base on natural materials	76
4.3	Mean of angle effect on standard deviation of angles sources errors.....	83
4.4	Mean of angle and distance effect of sum of angles sources errors.....	84
4.5	Standard Deviation against the Measured Distance	85
4.6	Standard Deviation of Latitude	88
4.7	Standard Deviation of Departure	88
4.8	Standard Deviation of Height	88
4.9	Coordinate differences in North Components	89
4.10	Coordinate differences in East Components.....	89
4.11	Coordinate differences in Height	90
4.12	The direction is azimuth angle of Monitoring target points	90