

List of Figures

Figure-1: Schematic diagram of the reactor for the photo oxidation of sulfide.....	32
Figure-2: Schematic diagram of a multi compartment device for UV light photo oxidation of sulfide.....	33
Figure-3: Schematic diagram of the set up for catalytic oxidation of sulfide.....	35
Figure-4: Schematic diagram of the set up for precipitation of sulfide.....	36
Figure-5: Schematic diagram of the aeration in the presence of ultrasonic vibration.....	37
Figure-6: Relationship between sulfide concentration and time in photo oxidation.....	38
Figure-7: Relationship between time and sulfate formed during photo oxidation of sulfide....	39
Figure-8: Relationship between time, pH and dissolved oxygen during the photo aeration.....	40
Figure-9: Relationship between time and concentration during oxidation at different air flow rates.....	41
Figure-10: Relationship between time and sulfate formed during oxidation at different air flow rates.....	41
Figure-11: Relationship between time and sulfide at different oxygen partial pressures.....	42
Figure-12: Relationship between time and sulfate formed at different oxygen partial pressures.	43
Figure-13: Relationship between time and sulfide during oxidation at different UV light intensities.....	43
Figure-14: Relationship between time and sulfate formed at different UV light intensities.....	44
Figure-15: Relationship between time and sulfide of industrial sample during oxidation.....	44
Figure-16: Linear plot of $\ln [d(S^{-2})/dt]$ against $\ln[S^{-2}]$	44
Figure-17: Linear plot of $\ln [d(S^{-2})/dt]$ against $\ln [O_2]$	45
Figure-18: Linear plot of $\ln [d(S^{-2})/dt]$ against $\ln[S^{-2}]^2[O_2]^{1.4}$	45
Figure-19: Linear plot of $\ln [d(S^{-2})/dt]$ against $\ln [O_2]$	46
Figure-20: Linear plot of $\ln[(SO_4)^{-2}/dt]$ against $\ln[S^{''}]$	46
Figure-21: Linear plot of $\ln [(SO_4)^{-2}/dt]$ against $\ln[S^{''}]^{0.92}[O_2]^{1.2}$	47
Figure 22.: FT-IR Spectrum of Ferric oxide.....	48
Figure-23: XRD spectrum of Ferric Oxide catalyst.	48
Figure-24: SEM picture of the ferric oxide catalyst at 20X.....	49

Figure-25: Relationship between time and sulfide during oxidation at different initial sulfide concentrations.....	50
Figure-26: Relationship between time and sulfide during oxidation process at different catalyst loading.....	51
Figure-27: Relationship between time and sulfide during oxidation process at different temperatures.....	52
Figure-28: Relationship between time and sulfide at different hydrogen peroxide addition.....	52
Figure-29: Relationship between time and sulfate formed at different initial sulfide concentrations.....	53
Figure-30: Relationship between time and sulfate formed at different catalyst loading.....	54
Figure-31: Relationship between time and sulphide at different temperatures.....	54
Figure-32: Linear plot between product of sulfide, catalyst and hydrogen peroxide and rate of sulfide oxidation.....	55
Figure- 33: Arrhenius plot of reaction rate for sulfide oxidation.....	55
Figure-34: Linear plot between sulfide and rate of sulfide oxidation on logarithmic scale.....	56
Figure-35: linear Plot for the determination of rate constant of sulfate formation.....	57
Figure-36: Time-concentration plots of sulfide removal.....	58
Figure-37: Time -concentration reduction plots of sulfide by iron salts at different initial sulfide concentrations.....	59
Figure-38: Time-concentration plots of sulfide reduction at different temperatures.....	59
Figure-39: Time-concentration plots of sulfide removal from industrial wastewater at different Fe^{+2}/Fe^{+3} ratios.....	60
Figure-40: Time-concentration plots of sulfide removal for industrial wastewater.....	60
Figure -41: Relationship between time and sulfide at different air flow rates.....	61
Figure-42: Linear fit of $\ln[d(S^{-2})/dt$ Vs $\ln[S^{-2}]$ at $Fe^{+2}/Fe^{+3} = 0.5$	61
Figure-43: Linear fit of $\ln[d(S^{-2})/dt$ Vs $\ln[S^{-2}]$ at $Fe^{+2}/Fe^{+3} = 0.3$	62
Figure-44: Linear fit of $\ln[d(S^{-2})/dt$ Vs $\ln[S^{-2}]$ at $Fe^{+2}/Fe^{+3} = 0.8$	62
Figure-45: Arrhenius plot for precipitation of sulfide at $Fe^{+2}/Fe^{+3} = 0.5$	63
Figure-46: SEM picture of the iron sulfide precipitate at 20X.....	63
Figure-47: XRD spectrum of the iron sulfide precipitate.....	64
Figure-48: FT-IR spectrum of the iron sulfide precipitate.....	64

Figure-49: Relationship between time and sulfide oxidized during oxidation at different initial sulfide concentrations.....66

Figure-50: Relationship between time and sulfide during oxidation at different air flow rate....67

Figure-51: Relationship between time and sulfide oxidized during oxidation at different ultrasonic vibrations.....67

Figure-52: Linear plot of $\ln[d(S^2)/dt]$ against $\ln[S^2]$ on logarithmic scale.....68

Figure-53: Linear plot of $\ln[d(S^2)/dt]$ against $\ln[\text{Air}]$ on logarithmic scale.....69

Figure-54: Linear plot of $\ln[(\text{Air flow rate})^{0.36} (S^2)^{1.9}]$ on logarithmic scale.....69

List of Tables

Table-1: Photo oxidation of 700ppm of sulfide at 4 watts and 4liter/min of air flow rate.....	86
Table-2: Photo oxidation of 500ppm of sulfide at 4 watts and 4liter/min of air flow rate.....	86
Table-3: Photo oxidation of 1030ppm of sulfide at 4 watts and 4liter/min of air flow rate.....	88
Table-4 Photo oxidation of 1300ppm of sulfide at 4 watts and 4 liter/min of air flow rate.....	88
Table-5 Photo oxidation of 1700ppm of sulfide at 4 watts and 6 liter/min of air flow rate.....	89
Table-6 Photo oxidation of 1700ppm of sulfide at 4 watts and 8 liter/min of air flow rate.....	89
Table-7 Photo oxidation of 1700ppm of sulfide at 4 watts and 2 liter/min of air flow rate.....	90
Table-8 Photo oxidation of 1700ppm of sulfide at 4 watts and 1liter/min of air flow rate.....	90
Table-9: Photo oxidation of 1700ppm of sulfide at 4 watts and 4liter/min of air flow rate having oxygen concentration of 30%.....	91
Table-10 Photo oxidation of 1700ppm of sulfide at 4 watts and 4liter/min of air flow rate having 40% oxygen concentration.....	91
Table-11 Photo oxidation of 1700ppm of sulfide at 4 watts and 4liter/min of air flow rate having oxygen concentration of 50%.....	92
Table-12 Photo oxidation of 1700ppm of sulfide at 4 watts and 4liter/min of air flow rate having oxygen concentration of 10%.....	92
Table-13: Photo oxidation of 1700ppm of sulfide at 8 watts and 6liter/min of air flow rate having oxygen concentration of 21%.....	93
Table-14: Photo oxidation of 1700ppm of sulfide at 12watts and 6liter/min of air flow rate having oxygen concentration of 21%.....	93
Table-15: Catalytic oxidation at 400 ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	94
Table-16: Catalytic oxidation at 600 ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	94
Table-17: Catalytic oxidation at 800 ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	95
Table-18: Catalytic oxidation at 1000ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	95
Table-19: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =1.5g).....	96

Table-20: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =0.5g).....	96
Table-21: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =2.6 ml and Catalyst =0.25g).....	97
Table-22: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =3.2 ml and Catalyst =1.00g).....	97
Table-23: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =3.0 ml and Catalyst =1.00g).....	98
Table-24: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at room temperature (H ₂ O ₂ =1.8 ml and Catalyst =1.00g).....	98
Table-25: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at temperature=45 ⁰ C (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	99
Table-26: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at temperature=35 ⁰ C (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	99
Table-27: Catalytic oxidation at 600ppm of sulfide by hydrogen peroxide at temperature=30 ⁰ C (H ₂ O ₂ =2.6 ml and Catalyst =1.00g).....	100
Table-28: Precipitation of sulfide at 2400 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.5 at room temperature (Industrial sample)	100
Table-29: Precipitation of sulfide at 2400 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.3 at room temperature (Industrialsample).....	101
Table-30: Precipitation of sulfide at 2400 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.8 at room temperature (Industrial sample).....	101
Table-31: Precipitation of sulfide at 4800 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.8 at room temperature (Industrialsample).....	101
Table-32: Aeration of sulfide at 600 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.5 at room temperature at air flow rate of 4liter/min (Industrial sample).....	102
Table-33: Aeration of sulfide at 750 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.3 at room temperature at air flow rate of 4liter/min (Industrial sample).....	102
Table-34: Aeration of sulfide at 520 ppm at Fe ⁺² /Fe ⁺³ ratio of 0.8 at room temperature at air flow rate of 4liter/min (Industrial sample).....	103

Table-35: Aeration of sulfide at 600 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at room temperature at air flow rate of 2 liter/min (Industrial sample).....	103
Table-36: Aeration of sulfide at 600 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at room temperature at air flow rate of 8 liter/min (Industrial sample).....	104
Table-37: Aeration of sulfide at 1328 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at room temperature at air flow rate of 4 liter/min (Industrial sample).....	104
Table-38: Precipitation of sulfide at 2400 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at temperature of 50 ⁰ C (Industrial sample).....	105
Table-39: Precipitation of sulfide at 2400 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at temperature of 50 ⁰ C (Industrial sample).....	105
Table-40: Precipitation of sulfide at 500 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at temperature of 40 ⁰ C (Synthetic sample).....	106
Table-41: Precipitation of sulfide at 500 ppm at Fe^{+2}/Fe^{+3} ratio of 0.5 at temperature of 65 ⁰ C (Synthetic sample).....	106
Table-42: Aeration of sulfide at 1000 ppm in the presence of ultrasonic vibration at 100% ultrasonic frequency and at 4 liter/min of air flow rate.....	107
Table-43: Aeration of sulfide at 800 ppm in the presence of ultrasonic vibration at 100% ultrasonic frequency and at 4 liter/min of air flow rate.....	107
Table-44: Aeration of sulfide at 600 ppm in the presence of ultrasonic vibration at 100% ultrasonic frequency and at 4 liter/min of air flow rate.....	108
Table-.45: DO and temperature change for respective initial sulfide concentrations.....	108
Table-46: Aeration of sulfide at 800 ppm in the presence of ultrasonic vibration at 60% ultrasonic frequency and at 4 liter/min of air flow rate.....	109
Table-47: Aeration of sulfide at 800 ppm in the presence of ultrasonic vibration at 20% ultrasonic frequency and at 4 liter/min of air flow rate.....	109
Table-48: DO and temperature change for respective different ultrasonic vibration frequencies.....	110
Table-49: Aeration of sulfide at 800 ppm in the presence of ultrasonic vibration at 100% ultrasonic frequency and at 6 liter/min of air flow rate.....	110

Table-50: Aeration of sulfide at 800 ppm in the presence of ultrasonic vibration at 100% ultrasonic frequency and at 2 liter/min of air flow rate.....111