

CERTIFICATION OF APPROVAL

**PERFORMANCE MEASURE FOR STEAM ABSORPTION CHILLER OF A
DISTRICT COOLING PLANT**

By

Siti Suhailah Binti Khairullah

A project dissertation submitted to
the Mechanical Engineering Programme
Universiti Teknologi PETRONAS
in partial fulfilment of the requirement for the
BACHELOR OF ENGINEERING (Hons)
(MECHANICAL ENGINEERING)

Approved by,

(AP Ir Dr. Mohd Amin bin Abdul Majid)

UNIVERSITI TEKNOLOGI PETRONAS

TRONOH, PERAK

MAY 2012

CERTIFICATION OF ORIGINALITY

This is to certify that I am responsible for the work submitted in this project, that the original work is my own except as specified in the references and acknowledgements, and that the original work contained herein have not been undertaken or done by unspecified sources or persons.

SITI SUHAILAH BINTI KHAIRULLAH

ACKNOWLEDGEMENTS

Praise be to Allah the Almighty upon the completion of this final year project within the time frame. My deepest gratitude and appreciation goes to my supervisor at Mechanical Engineering Department, AP.Ir .Dr. Mohd Amin bin Abdul Majid for his valuable advice during our meeting, relentless guidance and direction throughout the project timeline.

I would like to thanks for all that contribute in my final year project either directly or indirectly upon the completion of this project. I would also like to express my appreciation to the graduate assistant, Mr. Meseret Nasir Reshid for his guidance and support till the end of the project timeline. Last but certainly not the least, my beloved parents, Khairullah bin Nawawi and Seti Rakhiah binti Hamzah for their support, words of wisdom and relentless positive driving force.

ABSTRACT

The project focuses on development of reliability and availability model for steam absorption chiller at Universiti Teknologi PETRONAS Gas District Cooling (GDC) plant. Since failure data is not easily available, performance data is used to develop the model. The Markov model has been adopted. Historical performance data 2009 and 2010 for the steam absorption chiller has been used for analysis. Pareto Principle has been used to group the data in order to determine the number of states. Initial analysis indicates that the data could be divided into three groups; first group is between 850~1250 RTh, second group is between 450~850 RTh and the third group is between 0~450 RTh. Hence, the Markov model will have three states namely; state 2 with 850~1250 RTh, state 1 with 450~850 RTh and state 0 with 0~450 RTh. Using Markov model to develop multi-state system, the failure rate has been determined based on mathematical equation of Markov Chain and state space diagram. The availability and reliability graph were obtained using Matlab software based on differential equation method. The comparison for both results was also done using the traditional binary system which is BlockSim software. The availability results obtained between Matlab software and Block Sim software have small percentage different of 1.31% whereas the reliability result between Matlab software and Block Sim software have the high percentage different of 31.03%.

TABLE OF CONTENTS

ABSTRACT
CHAPTER 1:	INTRODUCTION								
	1.1	Background of Study	1
	1.2	Problem Statement	2
	1.3	Objective	2
	1.4	Scope of Research	2
	1.5	Relevancy of the project	2
	1.6	Feasibility of the project	3
CHAPTER 2:	LITERATURE REVIEW								
	2.1	Introduction	4
	2.2	Brief Description of Gas District Cooling	5
	2.3	Main Equipment of Gas District Cooling in UTP.	8
	2.4	Steam Absorption Chillers	11
	2.5	System Reliability	13
	2.6	Maintenance and Repair	15
	2.7	Pareto Analysis	16
	2.8	Markov Model.	17
CHAPTER 3:	METHODOLOGY								
	3.1	Project Planning	19
	3.2	Research Methodology	19
	3.3	Propose Model	21
	3.4	Model Assumption	21
	3.5	Pareto Analysis	21
	3.6	Estimation Method for Transition Rate	22
	3.7	State Space Modeling (Availability)	22
	3.8	Comparison with Block Sim Software	22
	3.9	Key Milestone on FYP 2	23
	3.10	Gantt Chart	24

	3.11	Tool/Software	24
CHAPTER 4:		RESULTS AND DISCUSSIONS	25
	4.1	Data collection	25
	4.2	Pareto chart	26
	4.3	Estimation of Transition rate	27
	4.4	State Space Modeling (Availability)	28
	4.5	Mathematical Equation (Availability)	30
	4.6	State Space Modeling (Reliability)	31
	4.7	Mathematical Equation (Reliability)	32
	4.8	Estimation State Probability.Availability,Reliability	34
CHAPTER 5:		CONCLUSION AND RECOMMENDATIONS	42
REFERENCES		44
APPENDICES		47

LIST OF FIGURES

Figure 1.1: The Bathtub Curve	5
Figure 2.1: Combined Heat and Power Plant (CHP)	6
Figure 2.2: An example of Trigeneration Plant	7
Figure 2.3: Block diagram of equipment Gas District Cooling system in UTP.	9
Figure 2.4: The main component of an absorption chiller	13
Figure 2.5: System Reliability for Repairable System	13
Figure 2.6: The assumptions for the condition of the system after repair stage	14
Figure 3.1: Project planning throughout the FYP timeline	19
Figure 3.2: Flow chart of performance measure of SAC	20
Figure 3.3: Parallel configuration for SAC system	21
Figure 4.1: The daily performance data for SAC	25
Figure 4.2: The Pareto chart for performance data clustering of SAC1 and SAC2	26
Figure 4.3: The state space diagram for one unit of SAC	27
Figure 4.4: Transition diagram of two unit chiller for availability.	29
Figure 4.5: Transition diagram of two unit chiller for reliability.	32
Figure 4.6: State probabilities of SAC system for availability.	36
Figure 4.7: The comparison of SAC system for availability	36
Figure 4.8: State probabilities of SAC system for reliability.	40
Figure 4.9: The comparison of SAC system for reliability.	40

LIST OF TABLES

Table 1.1: Major equipment of GDC plant at Universiti Teknologi PETRONAS.	8
Table 3.1: The bin used to calculate the frequency of group performance data	21
Table 3.2: Key Milestones for final year project FYP 2 . . .	23
Table 3.3: Gantt chart of FYP 1 and FYP 2	24
Table 4.1: The system state description for the SAC.	30
Table 4.2: The transition rate of the SAC system.	33
Table 4.3: State probabilities of SAC system for availability	34
Table 4.4: State probabilities of SAC system for reliability.	37