

### Relation between Antecedent Rainfall or Rainfall Amount with the Occurrence of Landslide in Universiti Teknologi PETRONAS

By

## Mohd Arif Bin Wan Mohd Dzulkifli

Dissertation submitted in partial fulfilment of the requirements for the Bachelor of Engineering (Hons) (Civil Engineering)

#### **JULY 2009**

Universiti Teknologi PETRONAS Bandar Seri Iskandar 31750 Tronoh Perak Darul Ridzuan

## CERTIFICATION OF APPROVAL

# Relation Between Antecedent Rainfall or Rainfall Amount With The Occurrence of Landslide in Universiti Teknologi PETRONAS

by

## Mohd Arif bin Wan Mohd Dzulkifli

A project dissertation submitted to the Civil Engineering Programme Universiti Teknologi PETRONAS in partial fulfilment of the requirement for the BACHELOR OF ENGINEERING (Hons) (CIVIL ENGINEERING)

Approved by,

(Dr. Rezaur Rahman Bhuiyan)

#### UNIVERSITI TEKNOLOGI PETRONAS

#### TRONOH, PERAK

July 2009

#### CERTIFICATION OF ORIGINALITY

This is to certify that I am responsible for the work submitted in this project, that the original work is my own except as specified in the references and acknowledgements, and that the original work contained herein have not been undertaken or done by unspecified sources or persons.

MOHD ARIF BIN WAN MOHD DZULKIFLI

Finally, I would like to these, my family. They have been a wonderful where of encountgrowent and joy to me and also not to forget the failout filends who's ingir herp was a transmission gift to me. May field bless all of us and only Hill, the Almighty could taper all my deten to them.

#### ACKNOWLEDGMENT

First and foremost, I give thanks and praise to God for His guidance and blessings throughout the entire course of my study.

I wish to express my gratitude to Dr Rezaur Rahman Bhuiyan, for his guidance and support throughout completing my Final Year Project in the Universiti Teknologi Petronas Civil Engineering Department. His knowledge is vital for the project that I had worked for. Without help from him, this Final Year Project may not be that meaningful and successful.

Greatest appreciation is also expressed to the following individuals, Dr. Hasnain, Miss Nurul Husna, Mr Kalai, Mr Meor, Dr. Indra Sakti, Dr Syed Baharom, and all staffs of Civil Engineering Department.

My acknowledgement would be incomplete without giving credit to Universiti Teknologi PETRONAS, especially Civil Engineering Department which has equipped me with essential skills for self-learning. Its well-rounded graduate philosophy has proven to be useful in the industry.

Finally, I would like to thank my family. They have been a wonderful source of encouragement and joy to me and also not to forget the fellow friends who's their help was a tremendous gift to me. May God bless all of us and only HE, the Almighty could repay all my debts to them.

#### Abstract

This study is presented to examine the relation between antecedent rainfall or rainfall amount with the occurrence of the landslide in Universiti Teknologi PETRONAS (UTP), Tronoh, Perak. The landslide had occurred near the Civil Engineering Block, Block 13, and caused a slight damage to that area. It was said that there were heavy rains for a few days before the event took place. Thus there is some possibility that the event might be caused by the rainfall. This study basically is to find out the effect of the rainfall (antecedent rainfall or rainfall amount) toward the occurrence of the landslide. The data of the rainfall for 2-year period had been obtained from the Hydrology and Water Resources of Department of Irrigation and Drainage Malaysia (DID) in order to perform this research. The data has been analyzed one by one and the result of the analysis shows the antecedent rainfall factor plays more important role than the triggering rainfall in this particular case.

## TABLE OF CONTENTS

ABSTRACT.	•	•	•		•	•	•	•		i
CHAPTER 1:		INT	ROD	UC	TION					1
		1.1	Ba	ackg	round	of Stu	dy.			1
		1.2	Pr	oble	m Sta	temen				5
		1.3	0	bject	ives a	and Sec	ope of Sta	udy	a for Las	7
CHAPTER 2:		LITI	ERA	TUI	RE R	EVIEV	v .	÷		8
CHAPTER 3:		MET	гно	DOI	LOG	Υ.				11
		3.1	Pr	ojec	t Acti	vities	•		10,165	11
		3.2	G	antt	Chart	and Ke	ey Milest	one	·	18
CHAPTER 4:		RES	ULT	SA	ND D	ISCU	SSION		•	20
CHAPTER 5:		CON	ICLI	USIC	ON A	ND RI	сомм	END	TION	28
REFERENCES	•	•						•		29
APPENDICES										31

### List of Figures

Figure 1.1. Damages caused by landslide at Bukit Antarabangsa.

Figure 1.2. Right view of Landslide in Universiti Teknologi PETRONAS.

Figure 1.3. Front view of Landslide in Universiti Teknologi PETRONAS.

Figure 1.4. Left view of Landslide in Universiti Teknologi PETRONAS.

Figure 4.1. Monthly rainfall in 2007 at (a) Rumah Pam Bota (b) Ladang Nalla

Figure 4.2. Daily rainfall data in October 2007 for (a) Rumah Pam Bota (b) Ladang Nalla

Figure 4.3. Accumulative of 11-days rainfall for the month of (a) June 2007 (b) July 2007 (c) October 2007 at Rumah Pam Bota.

Figure 4.4. Accumulative of 11-days rainfall for the month of (a) June 2007 (b) July 2007 (c) October 2007 at Ladang Nalla

Figure 4.5. The highest antecedent rainfall with elapsed time of 1-day, 3-day, 5-day, 7day, 9-day and 11-day at Rumah Pam Bota and Ladang Nalla through out of 2007.

## List of Tables

 Table 3.1. Milestone for the First Semester of 2-Semester Final Year Project

 Table 3.2. Milestone for the Second Semester of 2-Semester Final Year Project

## **Chapter 1: Introduction**

#### 1.1 Background of study

Nowadays, landslide is a common incident happened in many Malaysia and most of the tropical area in the world. For last few months, there were several landslide cases were reported in media. The latest was the tragedy of massive landslide that happened at Taman Bukit Mewah and Taman Bukit Utama in Bukit Antarabangsa, Kuala Lumpur. The catastrophe had destroyed many houses and properties around that residential area as shown in Figure 1.1. It also had killed many innocent people who live there. It was said that the main factor of this catastrophe was due to the heavy rain.



Figure 1.1. Damages caused by landslide at Bukit Antarabangsa

The Bukit Antarabangsa landslide is actually the third to occur in the Klang Valley in a week. On Nov 30, 2008, two sisters, were killed in a landslide which hit their bungalow in Ulu Yam Perdana, Gombak. On Thursday, a landslide in Jalan Semantan caused part of the retaining wall of a car park situated between two buildings to collapse, burying six cars and damaging five other vehicles. These landslides are believed to have been caused by movement of underground water and a condition made worse by the heavy rainfall in recent weeks. Actually there were more landslides had been occurred especially during the raining season. On Dec 11, 1993, one of three blocks of the 12-storey Highland Towers apartments collapsed killing 48 people.

This kind of tragedy can not afford to be happened again in the future because besides causing physical damages, it also can cause economic loss and this will give bad impression to the stability of national administration. Further action need to be taken and this has to be started with the investigation to find the major factor that leads to the landslide problem.

Basically, a landslide (or landslip) is a geological phenomenon which includes a wide range of ground movement, such as rock falls, deep failure of slopes and shallow debris flows, which can occur in offshore, coastal and onshore environments. Although the action of gravity is the primary driving force for a landslide to occur, there are other contributing factors affecting the original slope stability. Normally, pre-conditional factors build up specific sub-surface conditions that make the area or slope prone to failure, whereas the actual landslide often requires a trigger before being released.

There are many factors that can contribute to the landslide events. Actually, landslides are caused when the stability of a slope changes from a stable to an unstable condition. A change in the stability of a slope can be caused by a number of factors, acting together or alone. These are some of possible causes that can lead to the landslide events;

#### **Geological** causes

- Weak materials
- Sensitive materials
- Weathered materials
- Sheared materials
- Jointed or fissured materials
- Adversely orientated discontinuities

- Permeability contrasts
- Material contrasts
- Rainfall and snow fall

#### **Morphological causes**

- Slope angle
- Uplift
- Rebound
- Fluvial erosion
- Wave erosion
- Glacial erosion
- Erosion of lateral margins
- Subterranean erosion
- Slope loading
- Vegetation change

## Physical causes

- Intense rainfall
- Rapid snow melt
- Prolonged precipitation
- Rapid drawdown
- Earthquake
- Volcanic eruption
- Thawing
- Freeze-thaw
- Shrink-swell

- Ground water changes
- Soil pore water pressure
- Surface runoff
- Seismic activity

#### **Human** causes

- Excavation
- Loading
- Drawdown
- Land use change
- Water management
- Mining
- Quarrying
- Vibration
- Water leakage
- Deforestation

As mentioned before, most of the landslides tragedies in Malaysia were found occurred during the raining seasons. Thus there is high possibility that the main cause for the landslide is coming from the rainfall.

In this study, the rainfall (antecedent rainfall or rainfall amount) will be taken as the major factor to examine the cause for the landslide. It is hoped that it will help the authorities and all the related departments to come with some ideas in order to prevent this landslide problem or at least lessen its side effect.

#### **1.2 Problem statement**

Previously, a landslide had been occurred in Universiti Teknologi PETRONAS (UTP) at the hilly area near Block 13. As shown in Figure 1.2 - 1.4, the landslide was not really dreadful but yet it was still significant to engineering field as if there are no further action taken, this tragedy might be happened again and may be next time the impact will be greater.



Figure 1.2. Right view of Landslide.



Figure 1.3. Front view of Landslide.



Figure 1.4. Left view of Landslide.

There are many factors contribute to the landslide such as rainfall, initial water table location, geometry of the slope, and etc. It was said that a few days before the accident was happened, there was raining all day long. So, there was a possibility that the landslide was caused by that antecedent rainfall. A research will be conducted to find out is there any relation between the rainfall (antecedent rainfall or rainfall amount) with the slope stability that has made the landslide to be occurred.

## 1.3 Objective and scope of study

The objective of this study is to examine the relation between antecedent rainfall or rainfall amount with the occurrence of the landslide near the Block 13 in Universiti Teknologi PETRONAS (UTP). This study will cover the collection of rainfall data, data modeling and rainfall analysis.

This study only covers the effect of the rainfall to the landslide without considering any other soil properties factors.

The state of the second s

## **Chapter 2: Literature Review**

As been mention before, rainfall is one of the major factor that can cause landslide to take place. But it is still confusing on what kind of rainfall that can really cause this incident. Although the correlation between rainfall and landslides is widely recognized, there has been some debate as to the relative roles of antecedent rainfall and the triggering rainfall.

In the scope of landslide study, the antecedent rainfall is referred to the rainfall in the days right away preceding a landslide event. The triggering rainfall meanwhile is referred to the rainfall that falls at the time that the landslide occurs.

There are already some researches have been made to see and prove the effect of the antecedent rainfall on the slope stability. The researches show that the landslide might be occurred due the amount of the rainfall during the event, the antecedent rainfall or even including both of the factors.

Earlier, according to Brand (1984) through the researches made by him in Hong Kong, it is suggested that the antecedent rainfall was not a major factor to lead the landslide. Most of the landslides happened due to the short duration rainfall with a very high intensity. It was found that the 70mm/h of rainfall intensity would be enough to cause landslides in Hong Kong and a significant number of failures could be expected if the rainfall exceed 100mm/day. The limited influence of antecedent rainfall on landslides in Hong Kong was due to the high permeability of the local soils (Brand, 1992).

In Papua New Guinea, landslides might be happened if the rainfall intensity exceeds 70mm/h, as being suggested by Murray and Olsen (1988) and most of the major landslides occurred after 24 hour rainfall of 125mm. Major incidents would not be expected to occur until the rainfall reaches or exceeds the intensity of 100mm/day.

Pitts (1985) also concluded that the effect of the antecedent rainfall toward the slope stability in Singapore was not too much significant. However, Tan et al. (1987) re-examined Pitt's conclusions and suggested the otherwise; the antecedent rainfall could be significant in effecting the slope stability. Later, Chatterjea (1989) also came out with same conclusions. For the study case made by Wei et al. (1991) at Bukit Batok landslide in Singapore, it was found that the landslide occurred after a period of heavy rainfall but during the day of the landslide, there was no rainfall. This showed how the antecedent rainfall may affect the slope stability.

According to Rahardjo et al. (2001), the landslides that had occurred at Nanyang Technology University Campus in Singapore were due to the antecedent rainfall. From the investigation they made, it seemed that the antecedent rainfall during the five days before the event was significant in causing these landslides since other rainfall events of similar magnitude (but with less antecedent rainfall) did not cause landslides. In that study, any daily rainfall greater than 90mm must be followed by a 5-day antecedent rainfall exceeding 60mm first before it can initiate the landslides.

Unlike other researches, instead of using 5-day period, Lumb (1975) used a 15-day period to quantify antecedent rainfall for Hong Kong. It was still effective to prove the effect of the antecedent rainfall towards the slope stability. Later, the way he used was adopted by Tan et al for their study on the landslide in Singapore. However, Chartterjea (1989) suggested that such a long period might be inappropriate for the rainfall pattern in Singapore and he adopted a period of 5-days.

However, in the other research, also by Rahardjo et al. (2008), to identify the role of some controlling parameters (particularly the role of antecedent rainfall) in inducing instability of a homogenous soil slope, it is found that the significance of the antecedent rainfall depends on soil permeability. Yes, it is true that the effect of antecedent rainfall depends on soil permeability but for the investigation at area which have slightly same soil permeability; this parameter still can be considered as the main cause for the landslide.

By taking these journals as reference and main idea, a research will be done to identify the effect antecedent rainfall to the landslide that had happened at Universiti Teknologi PETRONAS (UTP) campus.

In engineering point of view, regardless the role of the soil permeability, the antecedent rainfall actually drives an increase in pore water pressures within the soil. This fluid pressure provides the block with buoyancy and later reducing the resistance to movement of the soil. It is happened when the slope fills with water. The fluid pressures then act down the slope as a result of groundwater flow to provide a hydraulic push and decrease the stability and further causing the landslide.

For examining the connection between antecedent rainfall or rainfall amount with the landslide occurrence, the rainfall data at the event area need first to be presented in graph. It is to ease the observation of the data.

The graph needs to be studied first and then identify the major storm events. If it is found that there is any daily rainfall that exceeds the rainfall record at day that the landslide was happened, but yet still produced no landslide, it means the landslide might be due to the antecedent rainfall. The accumulative rainfall for a certain period prior to a heavy-storm day also can be considered as the factor if the effect of antecedent rainfall can not be proven.

After the cause has been identified, further study on the soil properties also can be done to give more information about which types of soil might be affected to those factors.

## **Chapter 3: Methodology**

Determination of the effect of the antecedent rainfall toward land slide is to be done. The researches will be made through the internet, books and reliable articles or journals to collect all available information concerning the topic on the effect of antecedent rainfall on the slope stability. The collections of technical details regarding various researches on the subject will be used to implement and accomplish this project within the timeframe given.

#### 3.1 Project activities

This project will include the following activities:

#### 3.1.1 Acquiring Rainfall Data

To do this investigation, a data of rainfall records at the landslide area, for 2 years period at least, is needed. The rainfall records from January 2007 through January 2009 will be studied to identify major storm event as the landslide is assumed to fail early in 2009. The rainfall data needs to be gathered from reliable source so that a convincing result can be produced. The data can be obtained from:

- Hydrology Department of Universiti Teknologi PETRONAS (UTP) Civil Engineering Department
- Department of Irrigation and Drainage Perak

However, those departments can only provide at most up to one week period of rainfall data. For longer period data requirement, it needs to be obtained from Hydrology and Water Resources of Department of Irrigation and Drainage Malaysia (DID). The procedure of applying hydrological data from the DID is as follows;

- The applicant is requested to fill in the appropriate application forms (Form DI.1 (see Appendix 1) or Form DI.2) which are available in the DID website, http://h2o.water.gov.my. It is recommended that applicant refers to DID station inventory in order to determine the stations and period of data availability required during the process of filling-up the form.
- The applicant has to either fax the completed form to the given address or send it via E-mail.
- The application usually will be approved in one week.

As there is no specific rain gauge station placed at the occurrence place, the rainfall data from the nearest rainfall stations are requested. There are seven rainfall stations located around Universiti Teknologi PETRONAS which are;

- 1) 4308092
- 2) 4409090
- 3) 4409091
- 4) 4409121
- 5) 4410120
- 6) 4410122
- 7) 4410123

There is possibility that there might be some data missing in the provided data from the DID. If this is happened, the estimation of the missing data needs to be calculated.

If it is given that the annual precipitation values, P1, P2, P3, ..., Pm at neighbouring M stations 1, 2, 3, ..., M respectively, the missing annual precipitation Px at a station X

which is not included in the above M stations can be found by using some simple calculation.

If the normal annual precipitations at various stations are about 10% of the normal annual precipitation at station X, then arithmetic average procedure can be used to estimate the P<sub>x</sub>.

$$P_{x} = --- (P_{1}+P_{2}+...+P_{m})$$
M

If the normal precipitations vary significantly, then P<sub>x</sub> is estimated by using *normal ratio method*, byweighing the precipitation at the various stations by the ratios of normal annual precipitations.

$$N_x$$
  
 $P_x = --- [(P_1/N_1)+(P_2/N_2)+...+(P_m/N_m)]$   
M

Beside the rainfall data, the date of the occurrence of the landslide also needs to be obtained. The date is very important in order to further this study. The detail can be obtained from the Property Management and Maintenance Department of Universiti Teknologi PETRONAS.

#### 3.1.2 Modeling the Rainfall Records

After gathering the data from all those stations, the details will be modeled and presented by using hyetograph. According to K Subramanya, a hyetograph is a plot of the intensity of the rainfall against the time interval. It is usually represented as a bar chart. It is a very convenient way to show the characteristics of a storm.

Those data taken from the rain gauges actually only represent point sampling of the areal distribution of a storm. Thus, in order to convert the point rainfall values at the various stations into an average value over the catchment area, these three methods can be used;

- Arithmetical-Mean Method
- 2) Theissen-Mean Method
- Isohyetal Method

#### Arithmetical-Mean Method

This technique calculates areal precipitation using the arithmetic mean of all the point or areal measurements considered in the analysis. If P<sub>1</sub>, P<sub>2</sub>, ..., P<sub>i</sub>, ..., P<sub>n</sub> are the rainfall values in a given period in N stations within a catchment, then way to calculate the value of the mean precipitation or the effective depth P<sub>e</sub> over the catchment by the arithmetic-mean method is as follow;

- Sum the precipitation (P) at each station (1 through n).
- Divide the sum from (1) by the total number of stations (N). This will yield the effective depth of precipitation (P<sub>e</sub>)

$$(P_1+P_2+...+P_i+...+P_n)$$
 N  
 $P_e = ------= = (1/N) \sum P_i$ 

#### Theissen-Mean Method

This is another graphical technique which calculates station weights based on the relative areas of each measurement station in the Thiessen polygon network. The individual weights are multiplied by the station observation and the values are summed to obtain the areal average precipitation. The procedure of determining the weighing area is as follows;

- Connect each station to each nearby station with a straight line. These lines cannot cross and should connect only the nearest stations. If done correctly, you will form several triangles.
- 2) Each leg of the triangles formed in (1) is then bisected with a perpendicular line, thus forming polygons around each station. Draw over the lines defining the polygons with a RED pencil to avoid confusing them with other lines you have drawn.
- Using an appropriate method calculate the land area (A) represented by each polygon (1 through n) and record this area for each station.
- 4) Also calculate the total area (At).
- 5) Calculate the effective depth of precipitation (Pe) by the following formula:

 $P_{e} = \frac{P_{1}(A_{1}) + P_{2}(A_{2}) + \dots + P_{n}(A_{n}) \times A_{i}}{A_{1} + A_{2} + \dots + A_{n}} = \sum P_{i} - \dots - A_{i}$ 

#### Isohyetal Method

This is a graphical technique which involves drawing estimated lines of equal rainfall over an area based on point measurements. The magnitude and extent of the resultant rainfall areas of coverage are then considered versus the area in question in order to estimate the areal precipitation value. The procedure of determining the effective depth of precipitation is as follows;

- 1) The measured precipitation is recorded next to each station.
- 2) Using these values, neatly construct (n) isohyetals lines (contour interval = 2").
- 3) Calculate the area (A) between adjacent isohyetal lines (1-2,2-3,...,(n-1)-n).
- 4) Also calculate the total area (A1).
- 5) Calculate the effective depth of precipitation (Pe) by the following formula:

 $C_{1-2}(A_{1-2})+C_{2-3}(A_{2-3})+...+C_{(n-1)-n}(A_{(n-1)-n})$  $P_e=$ 

A

where C = depth of precipitation represented by adjacent isohyetal lines (1-2,2-3,..., (n-1)-n)

## 3.1.3 Analyzing Data

The data in the hyetograph will then be observed and analyzed in details one by one. From the observation made, the result will show exactly either the antecedent rainfall really causes the failure of the slope or not.

Let say if it is found that there is any daily rainfall that exceeds the rainfall record at day that the landslide was happened, but yet still produced no landslide, it means there was possibility that the landslide was occurred due to the antecedent rainfall. The accumulative rainfall for a certain period prior to a heavy-storm day also can be considered as the factor if the effect of antecedent rainfall can not be proven.

17

## 3.2 Gantt Chart and Key Milestone

# Table 3.1: Milestone for the First Semester of 2-Semester Final Year Project

No	Details/Week	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
1	Selection of Project Topic																
	- Research on Topic																
	- Confirmation of Topic Selection																
2	Preliminary Research Work																
	- Literature review																
	<ul> <li>Identifying methods used</li> </ul>																
3	Submission of Preliminary and Progress Report						•										
4	Project Work				-		-		-						-	_	-
	- Acquiring Data																
6	Seminar of FYP 1								•								
7	Project work continue																
	- Acquiring Data		_	_	_		_							_			
8	Submission of Interim Report Final Draft														•		
9	Oral Presentation	-	-	-	-	-	-	-	-	-	-	-	-	-	-	•	-
-	oral i reconstitution															-	
10	Submission of Interim Report																•



Suggested milestone

Process

No.	Detail/ Week	1	2	3	4	5	6	7	8	9	10	11	12	13	14
1	Project Work Continue														-
	- Modeling Data														
2	Seminar (compulsory)														
3	Submission of Progress Report 1						_	•							_
4	Project work continue													-	
	- Analyzing Data								_						
5	Poster Exhibition			_		_	_	_		_		•			
6	Submission of Dissertation (soft bound)									_		_	•		
7	Oral Presentation			_	_			_						•	
8	Submission of Project Dissertation (Hard Bound)														•

# Table 3.2: Milestone for the Second Semester of 2-Semester Final Year Project



Suggested milestone

Process

#### **Chapter 4: Results and Discussion**

From out of 7 the rainfall stations placed near the Universiti Teknologi PETRONAS (UTP), only 5 of them have the required details (daily rainfall data for 2007-2009) which are;

- 4309092 Rumah Pam Bota
- 4311001 Pejabat Daerah Kampar
- 4409091 Rumah Pam Kubang Haji
- 4409121 Ladang Nalla
- 4511111 Politeknik Ungku Omar

And from these 5 stations, only the data from 2 stations have been picked to proceed with the project which are 4309092 and 4409121 as the location of the stations are the nearest one to the UTP. The daily rainfall data from those two stations are shown in the appendix section (Appendix 2).

As the landslide was occurred on 23<sup>rd</sup> October 2007 (according to Property Management and Maintenance Department of UTP), only data from year 2007 was taken into consideration to be studied and analyzed in order to identify the major storm events at the landslide spot as the result that produced by later data (2008 and 2009) will give no relative effect to this research.

After transferring all the rainfall data from Rumah Pam Bota and Ladang Nalla into proper table, the data then was analyzed in detail. The more specific data (such as daily rainfall data, monthly rainfall data, accumulative of 11-days rainfall data and so on) were calculated one by one and each results were plotted in hyetograph or bar chart. This is to ease the data analyzing process. From the observation, it was found that the maximum monthly rainfall through out the year, at Rumah Pam Bota, was 403.0 mm in October while at Ladang Nalla was 350.0mm, also in October. From this fact, it can be assumed that the rainfall can be rated as one of the major factor for this landslide. The monthly rainfall records for 2007 at both stations are shown in Figure 4.1.







During the period before the event took place which was on 23<sup>rd</sup> October, there were several days in which the daily rainfall exceeded 70mm; 4 days at Rumah Pam Bota, these were 83.5mm on 21<sup>st</sup> January, 113.0mm on 14<sup>th</sup> June, 103.0mm on 26<sup>th</sup> July and 79.0mm on 22<sup>nd</sup> October, while at Ladang Nalla, it got 2 days, 79.0mm on 15<sup>th</sup> January and 71.0mm on 23<sup>rd</sup> July.

Those rainfalls were sufficient to cause a landslide on those days but there was no landslide occurred. More over, during the incident, the rainfall at Ladang Nalla station was very low which was only 9.0mm and even at Rumah Pam Bota, there was no rainfall at all. Figure 4.2 below shows the daily rainfall in October at both rainfall stations.



Figure 4.2. Daily rainfall data in October 2007 for (a) Rumah Pam Bota (b) Ladang Nalla

From the observation, it can be concluded that the landslide was not cause by the triggering rainfall. The landslide must be somehow due to the antecedent rainfall.

A data of accumulative rainfall had been made to find out the relation of the antecedent rainfall on the landslide and in this study case, the accumulation was taken up to 11 days. Figure 4.3 and 4.4 show the cumulative rainfall at Rumah Pam Bota and Ladang Nalla in three months which had highest monthly rainfall record through out the year which are June, July and October.

From the Figure 7, it clearly showed that 23<sup>rd</sup> October had the highest cumulative antecedent rainfall, 267.0mm, compared to the other days before that. At Ladang Nalla, even the cumulative antecedent rainfall on 23<sup>rd</sup> October, 243.0mm, was slightly lesser than some other days such as on 29<sup>th</sup> July (260.0mm) and on 30<sup>th</sup> July (251.0mm), but the amount was still extremely higher compared to the others. This can conclude that the antecedent rainfall did have a significant influence on the occurrence of the landslide.





Figure 4.3. Accumulative of 11-days rainfall for the month of (a) June 2007 (b) July 2007 (c) October 2007 at Rumah Pam Bota.



Figure 4.4. Accumulative of 11-days rainfall for the month of (a) June 2007 (b) July 2007 (c) October 2007 at Ladang Nalla.

This observation for the slope failure at the hilly area near the Block 13 in UTP suggests that the triggering rainfall or rainfall amount can not be the factor for this landslide occurrence as the daily rainfall on the day that the landslide was happened was totally very low.

The antecedent rainfall however does give a significant influence on the initiation of the landslide. In this case, an 11-days antecedent rainfall exceeding 260.0mm appears to have been sufficient enough to cause a landslide in UTP.

However, it should be noted that this conclusion is not the same as other observations obtained from the experiences in other places all over the world. For example, Brand et al. (1984) concluded that threshold value for major landslide in Hong Kong as 100mm while according to Rahardjo et al. (2001) in their study case in Singapore, the 90mm rainfall would be sufficient enough to create a landslide. These differences could be due to the different properties of soils in those particular areas.

However, this conclusion yet might have some other argument can be made. Some people said that the landslide might not be actually occurred on 23<sup>rd</sup> October 2007. The date of the landslide occurrence which was obtained from the Property Management and Maintenance Department of Universiti Teknologi PETRONAS (UTP) might not be accurate. Some people said the landslide was occurred earlier than 23<sup>rd</sup> October and the problem only being reported later (and in this case, on 23<sup>rd</sup> October).

If the statements were true, the exact date of the landslide occurrence should be laid on some where between 27<sup>th</sup> to 30<sup>th</sup> of July 2007. Base on Figure 4.5, most the highest antecedent rainfall with elapsed time of 1-day to 11-day fell on those dates. Thus there are some possibilities that the landslide might be actually occurred on those date.



Figure 4.5. The highest antecedent rainfall with elapsed time of 1-day, 3-day, 5-day, 7day, 9-day and 11-day at Rumah Pam Bota and Ladang Nalla through out of 2007.

### **Chapter 5: Conclusion and Recommendation**

In the end of this study, the research on the landslide that occurred near the Block 13 in Universiti Teknologi PETRONAS (UTP) on 23<sup>rd</sup> October 2007 indicates that the landslide was initiated by antecedent rainfall. The antecedent rainfall is one of important factors for the occurrence of the landslide. The total of 260mm 11-day antecedent rainfall appears to have been sufficient to cause a landslide in this case.

However, in this study, there are some important keys had been missing or taken for granted which had leaded the result to be not too accurate. In order to make this kind of research more successful, those things need to be stressed and taken into full attention;

- Exact date of the landslide occurrence This detail needs to be identified first before proceeding to other steps. This date will be the starting point to start analyzing the rainfall data. Without a certain date, the analyzing process will become harder and more complicated.
- Period of exanimate rainfall data 2-year period of daily rainfall data (at least) is required to make the research more accurate. With a longer period of data, more analyzed data can be compared so that the result that produced later will be more reliable.
- Rainfall data type The hourly rainfall data is the most preferable in order to conduct this kind of research. With the hourly data, the accuracy of the result will be higher.

## References

Brand, E. W. (1984). Landslides in Southeast Asia: a state-of-the-art report. Proceedings of the 4th International Symposium on Landslides. vol. 1. Canadian Geotechnical Society, Toronto. 17–59.

Brand, E. W. (1992). Slope instability in tropical areas. Proceedings of the 6th International Symposium on Landslides, Bell, D. H., (ed.), Balkema, Rotterdam, The Netherlands. pp. 2031–2051.

Chatterjea, K. (1989). Observation on the fluvial and slope processes in Singapore and their impact on the urban environment. PhD Thesis. National Univ. of Singapore, Singapore.

Lumb, P. (1975). Slope Failures in Hong Kong, Quarterly Journal of Engineering Geology, 8, 31-65.

Murray, L. M. and Olsen, M. T. (1988) Colluvial Slopes – A Geotechnical and Climatic Study, Proc. 2<sup>nd</sup> Int. Conf. on Geomechanics in Tropical Soils, Singapore, Vol. 2, pp. 573-579.

Pitts, J. (1985). An Investigation of Slope Stability on the NTI Campus, Singapore, Applied Research Project Report-RPI/83. Nanyang Technological Institute: Singapore; 54.

Rahardjo, H., Li, X. W., Toll, D. G. and Leong, E. C. (2001) The Effect of Antecedent Rainfall on Slope Stability, Geotechnical and Geological Engineering 19: 371-399.

Rahardjo, H., Rezaur, R. B. and Leong, E. C. (2008) Effect of Antecedent Rainfall on Pore-Water Pressure Distribution Characteristics in Residual Soil Slopes Under Tropical Rainfall, HYDROLOGICAL PROCESSES 22: 506-523. Rahardjo, H., Rezaur, R. B. and Leong, E. C. (2008) Role of Antecedent Rainfall in Slope Stability, Proceedings of the GEOTROPICA, Kuala Lumpur, Malaysia.

Subramanya, K. (1994) Engineering Hydrology Second Edition, Tata McDraw-Hill Publishing Company Limited, New Delhi, India.

Tan, S. B., Tan, S. L., Lim, T. L., and Yang, K. S. (1987). Landslide problems and their control in Singapore. Proceedings of the 9th Southeast Asian Geotechnical Conference. Vol. 1, Bankok, Thailand, pp. 25–36.

Wei, J., Heng, Y. S., Chow, W. C., and Chong, M. K. (1991). Landslide at Bukit Batok sports complex. Proceedings of the 9th Asian Conference on Soil Mechanics and Foundation Engineering. vol. 1. Balkema: Rotterdam; Bankok, Thailand. 445–448.

# Appendices

3	~	DOKUMEN K	UALITI	G. KELUARAN : 3
~	$\approx$			G. PINDAAN : .
BAHAG	IAN HIDROLOGI SUMBER AIR	BORANG PEMBEKAI HIDROLOGI OLEH	LAN DATA T.	ABIER EUATEUASA ; 01.04.00
	ISA-DK-DLI	PENGAIRAN DAN SALI PROJEK KERAJAAN / PE	IRAN UNTUK ENVELIDIKAN	RIKA SURAT : 1 dept. 1
		and the second sec		FORM DL1
	(Name of Applicant)	mette AP	HE B. When mot	DANKING DI
2.	No. Kad Pengenalan ( L.C.No. )	STOLOL	-03-5341	111111111111111111111111111111111111111
3.	JAWATAN BASMI (Official Designation)	STUPPN	т	
•	ALAMAT RASMI (Official Address)		KANDING BANA	
		15767. 84		LANTTHE .
8.	NO. TELEFON DAN (Talephone No. and E	E-MEL mail Address) 019-1551	HP / ritay P	scer007@ yelap cam
	NAMA PROJEK	Disst of	Antecedent K	unfall on Place Stability
7.	LOKASI PROJEK	(Industryality	Takanlani Dat	When (une) and Be
7.	LOKASI PROJEK (Locatian of Project) BUTIRAN DATA VC (Density of Data Repu	: University : DEPERLUKAN : :ww)	Tetaologi Pat	PANNAS (LITP), Transh, Per
7. a. Janin Dipartai	LOKASI PROJEK (Location of Project) BUTIRAN DATA YO (Densils of Data Ye (and Data ye and Type and Units of Data Required	Main Marshitti DI PERLURAN Iver) No. Storen atm Nama Storen/Storien No. or Name of Storien	Tempoh Data yang ipertukan/Fortad of Data Required	RAMAS (LATP), Transh, Per Kagaman Date Proposed Use (9 Date
7. Annin Diportal Chailiy	LOKASI PROJEK (Location of Project) BUTIRAN DATA YE (Desails of Date Repu don Units Of Date Repu don Units of Date of Date Reported	Hei USESHI DI PERLUKAN New Simen atas Name Simen Simen Mana Name of Station Clobar pt for UTP	Testenologi Part	RANAS (LITP), Transh, Per Keguman Date Proposed Use (Flame
7. Junin Diporta (	LORASI PROBEK (Location of Project) BUTHRAN DATA YC (Denails of Data Regu dan Unit Data yg an/Type and Units of Data Reguted Presenfull datas	: Universiti DI PERLUKAN Ins. Steven atm Name Steven/Station No. or Name of Station Classept is UTP 2.	Telefologi Par Tempeh Data yang jantukan/Pariod of Data Required Tanuary 2007 - 8 <sup>th</sup> Feleruary 2007	RAMAS (LITP), Transk, Per Kagaman Datai Proposed Use (9 June Turint Hear Project
7. R. Diquertain Diquertain Conciliy In the	LOKASI PROBEK (Location of Project) BUTERAN DATA YO (Details of Data Reput dan Unit Data ye and Unit Data ye and San data ye mainfield Anten mainfield Anten e ercent of the obore bot	: Mai USESSHA DE PERLUKAN : No. Samon atau Nama Samon Samon An. or Name of Station di Classage in UTP 14 Classage in UTP 2. brological data being supplied	Temped Data yong pertubation Period of Data Required " Incurry 2007 - 2" February 200 by the Department of In	RAMAS (LITP), Transh, Ren Kegman Date Proposed Use (Y Date Tubial Jean Project 9
7. Junits Diported Coulty In the spree	LORASI PROFEK (Location of Project) BUTTRAN DATA YO (Densite of Data Repu dan Unit Data yg and Tana Required Print Print	Mai VERSEA	Tempels Data yong Tempels Data yong ipartick and Person of Law Required " January 2007 - 2 <sup>10</sup> Pelerium y 200 by the Department of b	RAMAS (UTP), Transk, Ren Kegunaan Datel Proposed Use (9 Jame Tohns Henry Project of projection and Drainage, Fore
T. Annin Diportal Continy In the agree	LORASI PROFEK (Location of Project) BUTTRAN DATA YO (Densite of Data Report dan Unit Data yg and Type and Units of Data Reported Print Report full Andro e event of the obove how e to comply with the full (a) that the data	Hei VETSHA DI PERLUKAN None of Station None of Station Classept is UTP Classept is UTP Classept is UTP Classept is utp brological data being supplied ming conditions: to shall not be utilized for other	Tempels Data yong Tempels Data yong particle and Person of Law Required "Incurry 2007 - 2 <sup>th</sup> Faler Lawy 2007 by the Department of In r project or study under	RAMAS (UTP), Transk, Ren Kagaman Datai Proposed Use (9 June Torins Hanne Project of regation and Drainage, Fore as Jush application has been
T. Junits Disputed Concilly In the agree	LORASI PROFEK (Location of Project) BUTTRAN DATA YO (Densitie of Data Reput dan Unit Data yg and Tone and Units of Data Reputed Print Reputed Print Reputed Print Reputed (Data State State (of the observe layor to comply with the full (of their she da make to the (b) their sub-	Hei VERSEN DI PERLUKAN None of Station Name of Station All All All All All All All All All All	Tempoh Data yang Tempoh Data yang ipartakan/Period of Data Required I January 2007 - 8 <sup>th</sup> February 200 by the Department of In r project or study unles no obtained from the D	RAMAS (ATP), Transk, Ren Kagaman Datai Proposed Use Of Data Tohns Hear Project Tohns Hear Project a regation and Drainage, Dre as fresh application has been AD will be mitably made in
T. Junits Disputed Could y Jack da agree	LORASI PROBEK (Location of Project) BUTHRAN DATA YO (Densitie of Data Reput dan Unit Data yg and Tone and Units of Data Required manifesti Andro e recent of the observe hore e to comply with the full (a) that sate full (b) that automatic (b) that automatic (b) that automatic (b) that automatic (c) that automatic	Hei VERSEN DI PERLUKAN News) Name of Station Name of Station Name of Station Clobergh to UTP Divicipleal data being supplied inving conditions in shall no be utilized for other page or publication in which one notice on the the same of the de page or publication in which	Tempoh Data yang Tempoh Data yang ipartuk and Period of Data Required "Income 2007 - 8 <sup>th</sup> February 2007 by the Department of In r project or study under into obtained from the D mach data have been g condition 10 D for	RAMAS (ATP), Transk, Ren Kagaman Datai Proposed Use Of Data Tubint Hear Project Tubint Hear Project Trigation and Drainage, Due as fresh application has been AD will be entroby made in protect or utilized and a copy former on
7. B Diportal Diportal Contily In the agree	LORASI PROBEK (Location of Project) BUTHRAN DATA YO (Densite of Data Report dan Unit Data yg and Type and Units of Data Required manifedi Andro e recent of the observe how e to comply with the full (a) their the da match rep (b) their the da match rep (c) there also	I UNIVERSITY.	Tempeh Data yang Tempeh Data yang ipartuk and Period of Data Required <sup>1</sup> January 2007 - 8 <sup>th</sup> February 2007 by the Department of In r project or study unles no obtained from the D such data have been a standed to D.L.P. been a standed to D.L.P. been a standed to D.L.P. been a standed to D.L.P. been a	RAMAE (ATP), Tranch, Ren Kagaman Datai Proposed Use Of Data Tohni Hear Project Tohni Hear Project a fresh application has been AD will be entenbly made in pasted or utilized and a copy relaying an anony tok
7. B Diportal Contily In the agree	LOKASI PROFEK (Location of Project) BUTERAN DATA YO (Densite of Davis Report dan Unit Data ye and Topic and Lokas of Data Required Project Lang and Second Data Second and Second Data Second and Second Data Second (b) that the fail (b) that the fail (c) that the fail (c) that the fail	I UNIVERSITY.	Tempoh Data yang Tempoh Data yang ipuhahani Perind of Data Required "Incurry 2007 - 8 <sup>th</sup> Felerumy 200 by the Department of Is r project or study unles ma obtained from the D meth data have been q tembed to D1D, free og datas musit be skrough	RANAE (ATP), Tranch, Ren Kegmaan Data Proposed Use (Flam Trink Henry Project Trink Henry Project regation and Drainage, iver as fresh application has been 1.D. will be suitably made in moded or utilized and a copy feberge, on the Data Information Unit, be data Information Unit,
7. Marine Disported Consiliy An other agrees	LORASI PROFEK (Location of Project) BUTERAN DATA YO (Densite of Davis Report dan Unit Data ye and Topic and Lonis of Data Required reservent of the observe how a to comply with the foll (b) that the data made to the and the observe of such rep (c) that the data report of such rep	Hei USESSES DI PERLUKAN real) No. Stewen atm Nama Stewen/Station No. or Name of Station Classes to Large the UTP Classes to Large the UTP Dividence of Station Classes to Large the UTP Dividence of Station building conditions: In shealt mot be utilized for other to DLD. Independent for the use of the da paper or publication in which ort, paper on publication in which as that the ready for collection as that on arrangeoment came	Tempth Data yang iputhanifordial Otato Required I Incurry 2007 - 8 <sup>10</sup> Faleruncy 200 by the Department of In r project or study unles into obsistent from the D such data have been of shanked to D1D, for ag	Rightshik (ATP), Transki, Per Keguman Data Proposed Use (Y Law Tshint Hame Project Trightion and Drainage, i've so fresh application has been 1.D. will be suitably made in model or utilized and a copy federge, an the Date of application. Unit, he date of application. In the model, in the modified through
7. And a set of the se	LORASI PROFEK (Location of Project) BUTERAN DATA YO (Densite of Data Re- marking of Data Re- marking of Data Re- marking of Data Re- marking of the obove hou- to even of the obove hou- to comply with the follo- (b) that the data mark to the (b) that the data mark to the (c) that the data subplement	Hei USESSHA DI PERLUKAN real) No. Samon atm Nama Samon Jama Anna Anna Samon Jama Anna Anne of Status Classest in UTF 1" Classest in UTF 1" Classest in UTF 2" brokegiesed data being supplied ming conditions: In sheat not be attizzed for other to the DLD. redgement for the use of the de paper or publication in which or, paper on publication is a which or, paper on publication is a which or, paper on publication is a solit broken receipt of an anna date of colla- dates a far a new date of colla- tions a sheat for a new date of colla- tions a far a new date of colla- tions a new dat	Tempole Data yang Tempole Data yang iparkant/orised of Data Required "Incurry 2007 - I" Peleruary 200 by the Department of In r project or study under its obtained from the D such data have been g tended to D.I.D. free of data must be steringen within the superior of the option to be mat, the oppicer	RANNE (ATP), Tranch, Ren Kaguman Data Proposed Use (Flame Triving Hamer Project and Institute Project and Institute Project and Institute and a copy charge, an a copy constituted and a copy charge, an the Data Information Unit, he data of application in the and will be mailful through
7. And Departed 2 Could y As the agree	LOKASI PROFEK (Location of Project) BUTERAN DATA YO (Densits of Davis Report dan Unit Data ye and Unit Data ye and San Data ye and San Data ye that Reported Comments of the obove how to comply with the follow (b) that the data made to the data acknow of such rep (c) that the data ary report of such rep (c) that the data ary report of the ary ary report of the the data ary report of the ary ary of the data ary report of the ary ary of the of the data ary of the data ary of the data ary of the data ary of the data ary of the data ary of the data ary of the data ary of the data ary of the data ary of t	Hei USESSHA DI PERLUKAN real) No. Sawan atan Nama Sawan Shaman atan Nama Shamar Shaman Atan Shamar Galantan Classest to UTT 1 <sup>10</sup> Classest to UTT 1 <sup>10</sup> Classest to UTT 1 <sup>10</sup> 20 buildingload data being supplied integer on publication in which only and the set stitued for other in sheaft mot be attitued for other in the set of the same of the de paper or publication in which ori, paper on publication in which origination and investor of origination is shall be ready for collection which on origination is made	Tempoh Data yang Tempoh Data yang parkant/orised of Lana Required "Incurry 2007 - 2 <sup>10</sup> February 200 by the Department of It r project or study unles the obtained from the D such data have been g tended to D.I.D. free of data have be the opplica- tion for our weak from to the mest, the application from of the mest, the application	RANNE (ATP), Tranch, Ren Kaguman Data Proposed Use (Flame Triving Same Project Triving Same Project and Control Project and Co
7. And Departed 2 Caulty As the agree	LOKASI PROJEK (Location of Project) BUTERAN DATA VG (Densits of Dain Regen dan Unit Data yg and Type and Units of Dain Required memory of the obove how a comply with the fail (b) that the data made to the (b) that the data and regent (c) the the data an	Hei USESSHA DI PERLUKAN bedi Dis Samon aton Nama Samon Samon aton Nama Samon Samon Anno Anno Samon Samon Anno Anno of Samon Closes of Samon Samon Anno Samon	Tempoh Data yang Tempoh Data yang partubant/teriod of Data Required "Incurry 2007 - 2 <sup>10</sup> February 200 by the Department of Is r project or study unles into obtain have been of such data have been of such data have been of the obtained to D.I.D. free of data have be explored to be mut, the application the retire.	RANNE (ATP), Tranch, Ren Kaguman Data Proposed Use (Flame Trink Same Project Trink Same Project and Destinage, Fore as fresh application has been ALD will be missible made in model or willed and a copy febrage, on the date of application Inthe and will be metified through the date of application. The a spin.
2. Junit Dynamics Constity Jan she agrees	LOKASI PROJEK (Location of Project) BUTERAN DATA VG (Densits of Dain Report dan Unit Data yg and Unit Data yg and San Dain State (Dain Say San Data yg and San Dain State (Dain Say San Data yg and San Data yg and San Data yg and San Data yg and San San San (Dain San (Dain San San (Dain San) (Dain San (Dain San (Da	Hei USESSHA DI PERLUKAN bed Statest Status atte Neues Statest Status Ne. or Neue of Status Closest to UTF 1" Closest to	Tempoh Data yang Tempoh Data yang partubant/fortiad of Data Required 3 Sanuary 2007 - 2 Sanuary 2007 - 1 Sanuary 2007 - 2 Sanuary 2007 - 1 Sanuary 2	RANNE (ATP), Tranch, Ren Kaguman Data Proposed Use (g Data Trink Some Project regation and Drainage, Swe as firsh equilication has been AD will be mitably made in protect or will be mitably made in protect or will be mitably made in the date of application. In the and will be metified through to date of application. The approx

Appendix 1: Form DI.1 (Application form for acquiring hydrological data for the use of government project, research or academic)

Day	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.0	0.0	22.5	0.0	14.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	39.5	0.0	0.0	0.0
3	0.0	0.0	0.0	0.0	0.0	42.0	0.0	0.0	3.5	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	27.0	0.0	0.0	0.0	0.0	0.0	0.0
5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	7.0	0.0	0.0
7	18.0	0.0	0.0	0.0	0.0	0.0	19.5	0.0	15.0	15.0	11.0	0.0
8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	8.0	0.0	0.0
9	0.0	0.0	0.0	0.0	2.0	0.0	0.0	0.0	2.5	0.0	0.0	10.5
10	20.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	7.0	0.0
11	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
12	0.0	8.0	0.0	32.0	0.0	22.0	0.0	0.0	0.0	22.0	0.0	20.0
13	20.0	54.5	0.0	23.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
14	14.5	0.0	0.0	0.0	17.0	113.0	0.0	0.0	0.0	0.0	44.5	0.0
15	0.0	22.0	0.0	0.0	4.5	3.0	12.0	0.0	0.0	40.0	0.0	0.0
16	0.0	20.0	0.0	9.0	0.0	0.0	0.0	10.5	35.0	50.0	0.0	0.0
17	0.0	10.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
18	0.0	25.0	10.0	0.0	0.0	21.0	0.0	1.5	0.0	26.0	0.0	112.0
19	34.0	15.0	8.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0
20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	8.0	0.0	50.0	17.0	30.0
21	83.5	28.5	25.0	0.0	0.0	0.0	28.0	35.5	0.0	0.0	0.0	20.0
22	0.0	8.5	0.0	20.0	0.0	0.0	47.0	0.0	0.0	79.0	5.0	0.0
23	0.0	0.0	6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
24	0.0	10.5	0.0	31.0	27.5	0.0	30.0	0.0	0.0	15.0	6.5	0.0
25	0.0	8.0	0.0	0.0	7.5	0.0	5.5	0.0	0.0	6.0	0.0	0.0
26	9.0	0.0	0.0	21.0	52.0	0.0	103.0	0.0	0.0	0.0	0.0	0.0
27	0.0	0.0	0.0	7.5	10.0	0.0	12.0	0.0	0.0	61.0	0.0	0.0
28	0.0	0.0	0.0	25.5	0.0	0.0	31.0	0.0	0.0	0.0	0.0	0.0
29	0.0		14.0	40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
30	0.0		40.0	8.5	0.0	0.0	0.0	10.0	0.0	0.0	0.0	0.0
31	0.0		11.0		0.0		0.0	0.0		24.0		0.0
Total	199.0	210.5	136.5	217.5	134.5	228.0	288.0	65.5	95.5	403.0	91.0	193.5

## Appendix 2.1. Table of Daily Rainfall Data at Rumah Pam Bota for 2007

Day	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.0	0.0	0.0	0.0	0.0	5.0	0.0	0.0	25.0	0.0	0.0	0.0
2	9.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	7.0	0.0
3	0.0	0.0	27.0	21.0	0.0	35.0	50.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	1.5	0.0	0.0	50.0	4.0	0.0	0.0
5	7.0	0.0	35.0	16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	15.5
6	0.0	0.0	0.0	0.0	0.0	18.0	0.0	0.0	0.0	0.0	0.0	0.0
7	70.5	0.0	26.0	16.0	0.0	0.0	0.0	0.0	0.0	20.0	0.0	0.0
8	81.0	0.0	0.0	1.5	0.0	0.0	0.0	0.0	25.5	5.5	0.0	0.0
9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	15.0
10	37.5	0.0	39.0	18.0	0.0	8.0	0.0	0.0	52.0	90.0	38.0	10.0
11	0.0	0.0	36.0	0.0	0.0	0.0	0.0	0.0	3.0	35.5	0.0	12.5
12	0.0	0.0	110.0	100.0	0.0	0.0	0.0	20.5	0.0	0.0	60.0	14.5
13	0.0	0.0	0.0	20.0	0.0	0.0	0.0	0.0	0.0	25.0	23.0	10.0
14	0.0	0.0	25.0	43.0	0.0	0.0	100.0	0.0	5.0	4.0	0.0	50.5
15	8.5	0.0	0.0	0.0	0.0	0.0	17.0	0.0	0.0	30.0	0.0	0.0
16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	8.0	53.0	0.0
17	10.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	22.0	0.0	0.0
18	0.0	0.0	0.5	11.0	0.0	0.0	0.0	153.0	0.0	9.0	0.0	0.0
19	0.0	0.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	35.0	41.0	0.0
20	0.0	0.0	6.0	0.0	0.0	0.0	37.0	6.5	0.0	42.0	0.0	0.0
21	0.0	0.0	0.0	7.5	0.0	0.0	41.0	18.0	0.0	47.5	0.0	0.0
22	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
23	0.0	0.0	75.0	0.0	16.0	0.0	9.5	43.0	8.0	4.5	0.0	0.0
24	0.0	55.0	17.5	0.0	0.0	0.0	7.0	13.0	0.0	3.0	28.0	50.0
25	0.0	0.0	40.5	0.0	0.0	0.0	0.0	14.0	0.0	0.0	25.0	0.0
26	0.0	0.0	0.0	0.0	12.0	0.0	0.0	32.5	4.5	0.0	59.5	0.0
27	79.0	35.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
28	0.0	20.0	0.0	14.0	0.0	0.0	0.0	0.0	0.0	0.0	4.0	0.0
29	0.0	0.0	0.0	0.0	0.0	52.0	0.0	5.0	0.0	0.0	0.0	43.0
30	0.0		0.0	0.0	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
31	0.0		45.5		0.0		0.0	12.0		0.0		0.0
Total	303.5	110.0	487.0	268.0	53.0	119.5	261.5	317.5	173.0	385.0	338.5	221.0

## Appendix 2.2. Table of Daily Rainfall Data at Rumah Pam Bota for 2008

Day	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.0	17.0										
2	0.0	0.0										
3	0.0	0.0										
4	0.0	0.0			1. D.C.							
5	12.0	0.0										
6	0.0	0.0										
7	0.0	0.0										
8	13.0	0.0			1.1							
9	0.0	0.0										
10	0.0	0.0										
11	0.0	0.0										
12	0.0	0.0										
13	0.0	0.0										
14	39.0	0.0										
15	0.0	0.0										
16	0.0	0.0										
17	21.0	7.0										
18	0.0	0.0							1.0			
19	0.0	0.0			1							
20	0.0	20.0									1.	
21	0.0	0.0										
22	15.0	15.0										
23	0.0	0.0										1 1 1 1
24	0.0	12.5									1	1
25	13.0	7.0										
26	0.0	5.0										
27	0.0	0.0									1.1	
28	0.0	21.0										111
29	0.0											
30	0.0											
31	0.0											
Total	113.0	104.5										

## Appendix 2.3. Table of Daily Rainfall Data at Rumah Pam Bota for 2009

Day	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.0	0.0	46.0	43.0	0.0	0.0	0.0	0.0	48.0	0.0	0.0	6.0
2	0.0	0.0	0.0	0.0	0.0	52.0	0.0	0.0	56.0	0.0	10.0	0.0
3	0.0	0.0	0.0	0.0	0.0	37.0	0.0	0.0	4.0	0.0	0.0	0.0
4	0.0	0.0	0.0	8.0	0.0	45.0	7.0	0.0	1.0	0.0	0.0	0.0
5	0.0	0.0	1.0	0.0	0.0	6.0	0.0	0.0	0.0	0.0	3.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	7.0	0.0	0.0
7	20.0	0.0	0.0	0.0	0.0	0.0	2.0	0.0	19.0	11.0	3.0	10.0
8	2.0	0.0	0.0	0.0	0.0	8.0	5.0	0.0	3.0	3.0	6.0	4.0
9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.0	5.0	0.0	0.0
10	9.0	0.0	0.0	0.0	14.0	50.0	0.0	0.0	0.0	0.0	0.0	0.0
11	18.5	0.0	0.0	1.0	5.0	12.0	0.0	0.0	0.0	0.0	5.0	14.0
12	0.0	0.0	0.0	0.0	0.0	7.0	0.0	0.0	0.0	0.0	0.0	16.0
13	2.0	8.0	6.0	34.0	18.0	42.0	0.0	0.0	37.0	30.0	6.0	10.0
14	0.0	47.0	12.0	30.0	23.0	47.0	0.0	0.0	13.0	25.0	0.0	14.0
15	79.0	0.0	6.0	0.0	5.0	4.0	0.0	0.0	0.0	35.0	3.0	0.0
16	0.0	0.0	1.0	15.0	0.0	0.0	15.0	14.0	25.0	14.0	0.0	0.0
17	0.0	0.0	33.0	0.0	0.0	2.0	0.0	49.0	0.0	48.0	0.0	5.0
18	6.0	0.0	0.0	0.0	0.0	4.0	13.0	0.0	0.0	6.0	20.0	0.0
19	12.0	0.0	4.0	0.0	0.0	6.0	7.0	0.0	0.0	29.0	10.0	3.0
20	16.0	24.0	6.0	10.5	16.0	0.0	0.0	5.0	0.0	30.0	1.0	0.0
21	61.0	0.0	3.0	7.0	0.0	7.0	7.0	7.0	0.0	25.0	0.0	29.0
22	23.0	0.0	6.0	7.0	9.0	0.0	32.0	14.0	0.0	1.0	0.0	0.0
23	0.0	10.0	2.0	10.0	0.0	0.0	71.0	0.0	28.0	9.0	0.0	0.0
24	29.0	3.0	0.0	4.0	32.0	0.0	7.0	25.0	0.0	29.0	0.0	0.0
25	13.0	1.0	0.0	5.0	20.0	0.0	20.0	0.0	1.0	31.0	0.0	6.0
26	0.0	0.0	1.0	13.0	19.0	0.0	40.0	1.0	7.0	1.0	0.0	0.0
27	3.0	0.0	0.0	68.0	0.0	0.0	52.0	0.0	0.0	11.0	0.0	0.0
28	0.0	12.0	0.0	1.0	0.0	0.0	11.0	0.0	0.0	0.0	0.0	0.0
29	0.0		28.0	0.0	0.0	0.0	4.0	0.0	0.0	0.0	0.0	0.0
30	0.0		13.0	0.0	0.0	0.0	5.0	0.0	0.0	0.0	0.0	0.0
31	0.0		23.0		0.0		0.0	0.0		0.0		0.0
Intal	293.5	105.0	191.0	256.5	161.0	329.0	298.0	115.0	244.0	350.0	67.0	117.0

Appendix 3.1. Table of Daily Rainfall Data at Ladang Nalla for 2007

Dav	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.0	0.0	4.0	30.0	0.0	0.0	0.0	0.0	0.0	12.0	0.0	0.0
2	0.0	0.0	10.0	16.0	0.0	0.0	2.0	0.0	0.0	0.0	0.0	0.0
3	0.0	15.0	2.0	21.0	0.0	3.0	0.0	0.0	112.0	0.0	0.0	0.0
4	0.0	2.0	21.0	12.0	0.0	25.0	40.0	0.0	3.0	0.0	0.0	0.0
5	0.0	4.0	0.0	8.0	0.0	5.0	0.0	12.0	0.0	19.0	0.0	14.0
6	0.0	18.0	45.0	30.0	0.0	10.0	0.0	0.0	23.0	0.0	0.0	6.0
7	58.0	0.0	3.0	6.0	0.0	10.0	0.0	0.0	0.0	7.0	0.0	2.0
8	15.0	0.0	3.0	0.0	0.0	0.0	2.0	0.0	0.0	56.0	0.0	33.0
9	40.0	0.0	22.0	0.0	0.0	14.0	6.0	2.0	6.0	16.0	11.0	0.0
10	0.0	0.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	11.0	0.0	0.0
11	0.0	0.0	3.0	16.0	0.0	8.0	18.0	0.0	33.0	21.0	0.0	0.0
12	0.0	0.0	43.0	13.0	0.0	0.0	33.0	0.0	1.0	45.0	0.0	0.0
13	0.0	0.0	56.0	17.0	0.0	0.0	58.0	0.0	0.0	0.0	18.0	5.0
14	0.0	0.0	0.0	0.0	0.0	0.0	14.0	0.0	0.0	0.0	30.0	0.0
15	0.0	10.0	0.0	7.0	0.0	0.0	13.0	0.0	0.0	11.0	7.0	30.0
16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	35.0	32.0	9.0
17	0.0	25.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	7.0	0.0	25.0
18	5.0	10.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	27.0	78.0	0.0
10	5.0	4.0	19.0	0.0	19.0	3.0	0.0	0.0	0.0	6.0	0.0	8.0
20	30	0.0	16.0	7.0	0.0	2.0	0.0	135.0	0.0	19.0	34.0	0.0
24	20	0.0	0.0	20.0	0.0	0.0	26.0	3.0	0.0	21.0	0.0	0.0
22	0.0	0.0	35.0	0.0	1.0	0.0	1.0	20.0	0.0	15.0	37.0	0.0
23	0.0	0.0	28.0	7.0	0.0	4.0	0.0	0.0	0.0	3.0	15.0	0.0
24	0.0	0.0	30.0	0.0	28.0	2.0	51.0	21.0	0.0	3.0	5.0	0.0
25	48.0	0.0	14.0	4.0	4.0	0.0	9.0	30.0	0.0	4.0	6.0	0.0
20	0.0	0.0	37.0	0.0	1.0	0.0	0.0	3.0	0.0	0.0	3.0	0.0
20	0.0	0.0	41.0	0.0	0.0	0.0	0.0	15.0	0.0	0.0	0.0	0.0
20	20.0	72.0	0.0	0.0	0.0	0.0	0.0	58.0	0.0	0.0	0.0	0.0
20	0.0	0.0	0.0	3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	19.0
20	5.0	0.0	3.0	0.0	0.0	10.0	0.0	0.0	15.0	4.0	0.0	3.0
30	0.0		4.0		22.0		0.0	20.0		0.0		8.0
Total	201.0	160.0	443.0	218.0	75.0	96.0	273.0	319.0	193.0	342.0	276.0	162.0

Appendix 3.2. Table of Daily Rainfall Data at Ladang Nalla for 2008

Day	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	5.0	0.0										
2	2.0	6.0										
3	15.0	0.0										
4	0.0	0.0										
5	3.0	16.0										
6	0.0	36.0										
7	0.0	5.0										
8	0.0	0.0										
9	23.0	0.0										
10	0.0	0.0										
11	0.0	0.0										
12	0.0	15.0										
13	0.0	0.0										
14	10.0	0.0										
15	22.0	0.0										
16	0.0	0.0										
17	0.0	10.0										and the second second
18	42.0	0.0										
19	2.0	15.0										
20	0.0	0.0										
21	0.0	0.0										
22	22.0	20.0										
23	0.0	0.0										
24	0.0	35.0										
25	4.0	35.0										
26	0.0	2.0										
27	5.0	5.0										
28	5.0	2.0										
29	0.0											
30	0.0											
31	8.0											
otal	168.0	202.0										

## Appendix 3.2. Table of Daily Rainfall Data at Ladang Nalla for 2008