

X-10 Based Outdoor Light Automation System

by

Sapar Annayev

**Dissertation submitted in partial fulfillment of
the requirements for the
Bachelor of Technology (Hons)
(Information and Communication Technology)**

November 2007

**Universiti Teknologi PETRONAS
Bandar Seri Iskandar
31750 Tronoh
Perak Darul Ridzuan**

CERTIFICATION OF APPROVAL

X-10 Based Outdoor Light Automation System


by

Sapar Annayev

Dissertation submitted in partial fulfillment of
the requirements for the
Bachelor of Technology (Hons)
(Information Communication Technology)

November 2007

Approved By,



Mr. Low Tan Jung

Universiti Teknologi PETRONAS

Bandar Seri Iskandar

31750 Tronoh

Perak Darul Ridzuan

CERTIFICATION OF ORIGINALITY

This is to certify that I am responsible for the work submitted in this project, that the original work is my own except as specifies in the references and acknowledgments, and that the original work contained herein have not been undertaken or done by unspecified sources or persons.



Sapar Annayev

November 10, 2007

ABSTRACT

For “X-10 based Outdoor Light Automation” system the powerline is used as a medium of signal transmitting. There are two parts of the system: Receiver and Sender. Both parts should be plugged in to the sockets anywhere in the house, and each of them has a PIC16F877 to send, generate, receive signals and execute the appropriate instruction. It is already being widely practiced and used in the North America where they use 110V (60Hz), while the powerline standard in South East Asia is 240V (50Hz). The modular methodology is used to develop the system. This paper describes the process of developing “X-10 based Outdoor Light Automation” system using the 240V (60Hz) powerline as a medium of signal transmission and 5bits of data will be tested to switch on/off the device rather than 11bits that are used by existing X-10 communication protocol. Fewer bits in a message means that the transmission will be faster, fewer appliances will be controlled and less control functions would be used.

ACKNOWLEDGEMENT

First of all author would like to express deepest gratitude to Allah (c.c) for giving opportunity to live, for the mercifulness, support and guidance throughout Final Year Project.

The accomplishment of the Final Year Project “X-10 Based Home Automation System” is truly due to the support, help, cooperation and commitment of the people around, thanks for any commitment and any contribution they have done to this project.

Author would also like to express the highest gratitude to the project supervisor, Mr. Low Tan Jung for his great support and help throughout the whole project research and development period. The author also would like to express sincere thanks to the course mates and friends, who contributed by advising, motivating and supporting during both of the semesters.

The special appreciation goes to the author’s family and relatives for their love, support and encouragement and just for being beside!

Thank You.

TABLE OF CONTENTS

CERTIFICATION OF APPROVAL	i
ABSTRACT	ii
ACKNOWLEDGMENT	iii
CHAPTER 1:INTRODUCTION	1
1.1 Background of Study.....	1
1.2 Problem Statement.....	1
1.3 Objectives and Scope of Study.....	2
CHAPTER 2:LITERATURE REVIEW	4
2.1 Powerlines in home control systems.....	4
2.2 X-10 for Home Automation and Control.....	5
2.3 Analyses of X-10 in HCS.....	6
2.4 Performance of X-10 protocol	7
CHAPTER 3:METHODOLOGY	9
3.1 Stages in Methodology.....	9
3.1.2 System Design.....	10
3.1.3 Requirements Gathering.....	10
3.1.4 Design.....	10
3.1.5 Implementation.....	10
3.1.6 Testing.....	10
3.1.7 Module Integration & Testing.....	10
CHAPTER 4:RESULTS AND DISCUSSION	11
4.1 Module Development.....	11
4.1.1 Dual-polarity Power Supply.....	11
4.1.2 Signal Extractor.....	12
4.1.3 Signal Generator.....	13

4.1.4 Zero Crossing Detector.....15

4.1.5 Mains Coupling.....16

4.1.6 Transmission of 5 bit data.....16

CHAPTER 5: CONCLUSION AND RECOMMENDATION.....20

5.1 Conclusion.....20

5.2 Recommendation.....20

REFERENCES.....22

APPENDICES.....24

LIST OF FIGURES

Figure 1.1: 120 KHz bursts on 60 Hz signal	2
Figure 2.1: Bursts during the zero-crossing	5
Figure 3.1: Modular Methodology Diagram	9
Figure 4.1: System Block Diagram	11
Figure 4.2: Power Supply Circuit	12
Figure 4.3: Signal Extractor Circuit.	12
Figure 4.4: Before (left) and after (right) 120 KHz signal was sent through circuit	13
Figure 4.5: 50Hz input of the circuit (left), Empty output of the circuit (right)	13
Figure 4.6: Signal Generator Circuit	14
Figure 4.7: Code for Signal Generator	14
Figure 4.8: The 120 KHz PWM output (16F877)	15
Figure 4.9: Zero Crossing Detector Circuit	15
Figure 4.10: 120 KHz bursts on 50Hz signal	16
Figure 4.11: Testing the Zero Crossing Detector program using the PIC simulator.	16
Figure 4.12: 5-bit code	17
Figure 4.13: Sending "11010"-switch Off command	18
Figure 4.15: Sending "ON" signal. (11011)	19
Figure 4.16: Sending "OFF" and "ON" signals. (11010 and 11011)	19

CHAPTER 1

INTRODUCTION

1.1 Background of Study

Home Automation was all the time in the center of attention of the people, as everyone strives to live as easy as possible, to make life as simple as possible. With the latest technology advancements humans have a variety of ways to control equipment or any appliance remotely. One of the ways is to transmit the signal using the X-10 communication protocol.

X-10 based Home Automation systems were first used in 1970's, and became one of the most popular and widely used protocols in the home automation industry of North America. Its identity is the use of the power line as a transmission medium where the signal is sent during the extremely short period of zero-crossing of the power line's signal. On the other side, the receiver decides on the action based on the combination of the bits received.

1.2 Problem Statement

Home automation depends on communication protocols which are created to control the various electrical and electronic systems in your house. There are four main home automation players out there, each a little different, and they're not all compatible with each other.

X-10 is a well-established home automation technology which is more than 30 years old. With X-10, there's no need for new wiring because it transmits signals over existing power line. However, this can make it susceptible to interference.

The "X-10 based Outdoor Light Automation" system that is to be developed is briefly described here. As was mentioned above, there will be Sender and Receiver parts, and both of them will have a 16F877 PIC built in. On the Sender part, the light

sensor will serve as an input, and send the bits to Receiver to either switch ON or OFF the lights.




Figure 1.1: 120 KHz bursts on 60 Hz signal

The bits are transmitted in a batch of 11 bits (X-10 Communication Protocol), two times (for error checking). The PIC on the “Sender” side will generate a signal of 120 KHz, and transmit it during the Zero-Crossing interval.

1.3 Objectives and Scope of Study

1.2.1 Objectives

The objectives of the project are as follows:

- a) To build the X-10 based product applicable to Malaysian Standard.
- b) To make 5 bit data sufficient to switch ON/OFF the device.
- c) To build the flexible X-10 based System.

1.2.2 Scope of Study

The project scope includes the following:

- 1) To carry out study on the Home Automation and X-10 communication protocol.
- 2) To observe the pros and cons of the X-10 based Automation
- 3) To develop and build both the Sender and Receiver for X-10 based Automation.

1.2.3 Feasibility of the Project within the Scope and Time frame

Due to lack of experience and hazard in developing and implementing the mains coupler, the System Integration and Testing task is left for the future enhancements. Nevertheless the theoretical research, development and testing of the rest of the modules is performed and is explained in this report.

The scope and Gantt chart (Please refer to Appendix J) of this project has been deliberately arranged in order to fulfill the requirements throughout two semesters of the Final Year Project. In case any problem faced, the supervisor was seeked for advices.

CHAPTER 2

LITERATURE REVIEW

2.1 Powerlines in home control systems

In this chapter, I will focus on suitability of the X-10 for Home Automation and Control. Home Control System (HCS) is an integration of the following technologies: home networking, smart appliances, the internet, and mobile. Home networking is the collection of elements that process, manage transporting and store information, enabling the connection and integration of multiple computing, control, monitoring and communication devices in the home. Home networking, in turn, has been enabled by the emergence of new trends such as broadband access, telecommuting, multi-PC households, remote home security services, remote home energy services, and even remote assistive solutions for disabled people. (*Chunduru & Subramanian, 2007*)

Smart appliances is a relatively newer development and several major appliance manufacturers (Toshiba, Samsung, LG, and Carrier) are developing internet-ready appliances such as stoves, refrigerators, washers, dryers, and the microwave, so that these smart appliances may be directly plugged-into the home network. (*Chunduru & Subramanian, 2007*) Once these smart appliances are plugged-in, they become another element in the home network and may be controlled via the controller, either from outside or the inside of the home. Internet has really helped propel the ability of remote control facility of the HCS.

Therefore, HCS provides unprecedented level of control to the home owner and as a result may increase the quality of his or her life. The distinguishing features of the data sent over the HCS system are the following:

1. Short bursts of control commands from the controller
2. Short bursts of response commands from the appliance or equipment
3. Typically several nodes connected to the system, where the node refers to a controller, appliance, or equipment
4. Typically long average distance usually measured in tens of feet
5. Occasionally large data transmissions

2.2 X-10 for Home Automation and Control

One of the technologies widely used for HCS is X10 protocol which is used for data transmission. The X10 protocol is perhaps the oldest standard for home networking. It was introduced in 1978 for the Sears home control system and the Radio Shack plug'n'power system. (Chunduru & Subramanian, 2007)

X10 communicates between transmitter and receiver by sending and receiving signals over the power line wiring. These signals involve short RF bursts which represent digital information.




Figure 2.1: Bursts during the zero-crossing.

This protocol has many advantages including being inexpensive, no new wiring required, simple to install, compatible with many products, controls up to 256 devices. Household electrical wiring is used to send digital data between X10 devices. This digital data is encoded onto a 120 kHz carrier which is transmitted as bursts during the relatively quiet zero crossings of the 50 or 60 Hz AC alternating current waveform. One bit is transmitted at each zero crossing. The digital data consists of an address and a command sent from a controller to a controlled device. Controllers query equally advanced devices to respond with their status. This status may be as simple as "off" or "on", or the current dimming level, or even the temperature or other sensor reading. Devices usually plug into the wall where a lamp, television, or other household appliance plugs in; however some built-in controllers are also available for wall switches and ceiling fixtures. The relatively high-frequency carrier frequency carrying the signal cannot pass through a power transformer or across the phases of a multiphase system. (Cole and Tran, 2002)

In addition, because the signals are timed to coincide with the zero crossings of the voltage waveform, they would not be timed correctly to be coupled from phase-to-phase in a three-phase power system. Transmissions synchronized to zero crossing. For split phase systems, the signal can be passively coupled from phase-to-phase using a passive capacitor, but for three phase systems or where the capacitor provides insufficient coupling, an active X10 repeater is sometimes used. It may also be desirable to block X10 signals from leaving the local area so, for example, the X10 controls in one house don't interfere with the X10 controls in a neighboring house. In this situation, inductive filters can be used to attenuate the X10 signals coming into or going out of the local area.

2.3 Analyses of X-10 in HCS

Based on some literature review X10 may have negative impacts on the performance of HCS for the following reasons: (*Chunduru & Subramanian, 2007*):

1. Time to respond to the user is fast for short distances however, over the typical average long distances between the controller and the appliance encountered at home, the time to respond increases rapidly; the signal is sometimes so weak at the receiver that the receiver is not able to detect the signal at all.
2. Cost is usually low since no connectors need be installed between the controller and the appliance – however, amplifiers and noise filters are needed to send signals properly to distant nodes on the network and this quickly drives up the cost.
3. Ease of use may initially appear to be a strong point of the X10 technology – however, if the signal attenuation due to distance and line quality is significant then the system may well become unusable.
4. This technology is only accessible from home and not from outside – some form of converter will need to be used between outside connections and internal wiring; for example, if one requires that an appliance respond to commands from laptop in the homeowner's office, then the commands will have to be received over DSL or cable modem at the home and converted into X10 signals for transmission over home wiring which not only adds to the cost but could also result in undesirable delays.

5. Presence of noise and other disturbances on the power lines significantly impact the performance of HCS negatively: X10 devices such as lights are triggered randomly without any control command being sent to them. Heating pads and fluorescent lights also seem to affect X10 devices. An experiment that used a USB connection between the computer and the power line also did not alleviate the problems due to power line disturbances.

X-10 based transmitters send a specially coded low-voltage signal that is superimposed over the 240 volts on the home's electrical wires. A transmitter is usually capable of sending up to 256 different addresses on the AC line. Multiple transmitters can send signals to the same module.

Devices with specific symbol receive the special signals sent by the transmitters. Once a matching signal comes in, the device responds and turns ON or OFF or dims or brightens. Receivers generally have "code dials" that are adjusted by the user to set the address. Multiple devices with the same address can co-exist in the same home. These devices both send and receive X10 signals. Like regular receivers and transmitters, they can communicate on all 256 addresses

2.4 Performance of X-10 protocol.

The performance of X10 depends on several factors apart from its advantages including being inexpensive, no new wiring required, simple to install, compatible with many products, controls up to 256 devices it has many drawbacks as well. The drawbacks of X10 are signals from a transmitter in one live conductor may not propagate through the high impedance of the distributed transformer winding to the other live conductor. Often, there's simply no reliable path to allow the X10 signals to propagate from one phase wire to the other; this failure may come and go as large 240 volt devices such as stoves or dryers are turned on and off. (When turned on, such devices provide a low-impedance bridge for the X10 signals between the two phase wires.) This problem can be permanently overcome by installing a capacitor between the phase wires as a path for the X10 signals; the manufacturers commonly sell signal couplers that plug into 240 volt sockets that perform this function. More sophisticated installations install an active repeater device between the phases, while

others combine signal amplifiers with a coupling device. A repeater is also needed for inter-phase communication in homes with three-phase electric power.

Some X10 controllers may not work well or at all with low power devices (below 50 watts) or devices like fluorescent bulbs that do not present resistive loads. Use of an appliance module rather than a lamp module may resolve this problem. X10 signals can only be transmitted one command at a time. If two X10 signals are transmitted at the same time, they will collide and the receivers will not be able to decode the signal commands.

The X10 protocol is also slow. It takes roughly three quarters of a second to transmit a device address and a command. (*Chunduru & Subramanian, 2007*) While generally not noticeable when using a tabletop controller, it becomes a noticeable problem when using 2-way switches or when utilizing some sort of computerized controller. The apparent delay can be lessened somewhat through the use of scenes and by using slower device dim rates.

CHAPTER 3

METHODOLOGY

3.1 Stages in Methodology:

For this Final Year Project, the modular methodology is used. Total, there are 5 modules to design and build: Transformerless Power Supply (5V), Signal Generator, Signal Extractor, Zero-Crossing Detector and TRIAC. For each of the modules, stages like Information Gathering, Design, Implementation and Testing were carried out separately. And the last stage was be the most critical - Module Testing and Integration Stage.




Figure 3.1: Design Phases

3.1.1 Gather Information

During this stage the information about the X-10 was collected, and reviewed in detail. The pros and cons of implementing the X-10 communication protocol for the Home Control System were analyzed. The X-10 and Home Automation research works and projects were sieve through, which were mentioned in the Literature and Review chapter.

3.1.2 System Design

The overall system's block diagram was prepared. The system Sender and Receiver are made up of 5 circuits: Signal Generator, Signal Extractor, TRIAC, Zero-Crossing Detector and Transformerless Power Supply. The estimated deadlines for each of the modules were calculated.

3.1.3 Requirements Gathering

Based on the study, the list of the required components is prepared and similar function circuits were found to adapt for the project.

3.1.4 Design

Some similar function circuits were used to make them compatible with the local powerlines standards.

3.1.5 Implementation

The circuits were built on the breadboard, and tested using relevant test gears (oscilloscope, multimeter...etc) for the respective functionality.

3.1.6 Testing

The circuits were tested using the oscilloscope, multimeter, logic probe etc. After all the successful testings of the modules, circuits will be soldered.

3.1.7 Module Integration & Testing

The final testing, when all the modules passed the functional test, this is the last testing to identify the problems with any of the modules. Final touch-up to the whole system will commence right after this stage.

It also requires adding the mains coupling circuit to transmit the 120 KHz (5V) signal over the powerline.

CHAPTER 4

RESULTS AND DISCUSSION

4.1 Module Development

In this section the development of Signal Generator, Signal Extractor, Transformerless Power Supply and Zero Crossing Detector modules will be discussed. There is a TRIAC module which was supposed to be built the last. On the Figure 4.1 you can see the Block Diagram of the whole System, which gives a better picture of how, what and where the modules are connected.




Figure 4.1: System Block Diagram

4.1.1 Dual-polarity Power Supply

This module is required to provide circuits with the $\pm 5V$. Most of the electronic components require just $+5V$ and Gnd, but for the operational amplifiers there should be $-5V$ instead of grounding.




Figure 4.2: Power Supply Circuit

In the circuit, it can be observed that on the left there is a transformer converting from 240V to 12V, and to convert from 12VAC to +/-5VDC the full wave rectifier is used, with two voltage regulators. The heat sink is used to avoid any overheating of the voltage regulators.

4.1.2 Signal Extractor

Signal Extractor module will be placed on the Receiver side. It is the most complex circuit in the system. By referring to the existing circuits on the web and consulting some lecturer from EE department, I have adapted the circuit to fit to 240V. (For the circuit, please refer to Appendix F)




Figure 4.3: Signal Extractor Circuit.

Signal Extractor circuit has several functionalities such as:

- to cut the 50Hz frequency of the Powerlines
- to pass the 120 kHz signal

Testing was done using the Function Generator by Instec GFG, and Oscilloscope Tektronix. Below you can observe the results of the testing the circuit at different points.

As the output of the circuit goes straight to the PIC, it should produce either 0 or 1. As you can see below whenever there is 120 kHz signal appears on the input, there is output becomes '1'. Meaning the test was successful.




Figure 4.4: Before (left) and after (right) 120 kHz signal was sent through circuit. And when there is 50 Hz signal on the input of the circuit, it is seen below that it does not affect the output of the circuit.




Figure 4.5: 50Hz input of the circuit (left), Empty output of the circuit (right)

4.1.3 Signal Generator

The PIC16F877 has a CCP1 and CCP2 pins, where the last 'P' stands for Pulse Width Modulation (PWM). Since the CCP1 pin is multiplexed with the PORTC data latch, the TRISC<2> bit must be cleared to make the CCP1 pin an output. There are several registers that affect the result of the PWM, they are PR2, CCPR1L, CCP1CON<5:4> bits and T2CON. To calculate the values of the above mentioned registers, the online available PWM calculator was used. [3. PWM Calculator]




Figure 4.6: Signal Generator Circuit

The code to have PIC generating the 120 kHz signal is really simple, all we need to do is just set several registers to the particular value. The registers required are mentioned above, and here is the coding in Assembly:

```

PROCESSOR 16f877
#include "P16F877.INC"
__CONFIG_CP_OFF & _WDT_OFF & _HS_OSC
org 0x00
goto Main
org 0x04
goto Main

Main bcf STATUS,RP1
      bsf STATUS,RP0 ;Select Bank1
      movlw 0x00 ;Port C as output-CCP1 and CCP2 are on Port C
      movwf TRISC
      movlw 0x00
      movwf OPTION_REG
      movlw 0x10 ;set the upperlimit for the timer2
      movwf PR2
      bcf STATUS,RP1
      bcf STATUS,RP0 ;select bank 0
      movlw 0x04 ;set the prescaler and enable the timer2
      movwf T2CON
      movlw 0x08 ;set the dutycycle
      movwf CCPR1L
      movlw 0x1C ;set the dutycycle
      movwf CCP1CON

      END

```

Figure 4.7: Code for Signal Generator

The square wave 120 kHz signal was tested using the oscilloscope, and you can observe the signal from the Figure 4.8.




Figure 4.8: The 120 kHz PWM output (16F877)

4.1.4 Zero Crossing Detector

INTCON and OPTION_REG registers are playing the main role in setting the external interrupt. External interrupt on the RB0/INT pin is edge triggered, either rising, if bit INTEDG (OPTION_REG<6>) is set, or falling, if the INTEDG bit is clear. When a valid edge appears on the RB0/INT pin, flag bit INTF (INTCON<1>) is set. This interrupt can be disabled by clearing enable bit INTE (INTCON<4>).




Figure 4.9: Zero Crossing Detector Circuit

The input will be 12VAC (the output of transformer), if we select a resistor of $0.4M\Omega$, $12/0.4=30mA$, which is well within the current capacity of a PICmicro MCU I/O pin.




Figure 4.10: 120 kHz bursts on 50Hz signal

In order to send the bit every zero-crossing of the powerline signal, the INTEDG register is toggled on the falling and rising edge of the alternating powerline signal. During first few cycles interrupt will synchronize and later the pin C0 was changing with the rising and falling edges of the signal input at B0/Int. To test the Zero-Crossing Detector program the MPLAB IDE and PIC Simulator softwares were used. The coding is written in Assembly language, and did not exceed the 50 lines, you can have a look at Appendix H.




Figure 4.11: Testing the Zero Crossing Detector program using the PIC simulator.

4.1.5 Mains Coupling

The output is coupled to the mains via 1:1 isolating transformer T2. Coupling capacitors have a high reactance (318k) at 50Hz falling to only 160Ohms at 120 kHz. It is essential to use the high voltage capacitors because they must withstand the peak mains voltage. Transient suppressor TS1 protects the BJT Q1 from spikes of more than 10V.

The mains coupling has not been tested, but has been edited from the one used by the Andrew Holme in his Wireless Thermostat project in 2004. Due to the lack of experience and knowledge in electrical area, a main coupling is left for future enhancements.

For the full circuit of the Sender and Receiver please refer to the Appendix C and D.

4.1.6 Transmission of 5 bit data

One can ask, how both sender and receiver can be synchronized, the answer is that system uses bits to synchronize. The protocol is asynchronous as it is not necessary to send clocking information with the data that is sent.

The protocol is character oriented, and transmission is carried out without continuous character synchronization between the transmit and receive devices. Each group of data should be identified separately, and hence the beginning should be marked. Instead of having transmit and receive clocks connected, the receiver synchronized itself based on the start bit.

As it was mentioned above, one of the disadvantages of X-10 is slowness of transmitting data. Initially X-10 protocol was designed to have 11 bits, where the first 4 bits serve for the start code, the next 4 bits for address purpose (as each of the appliances in the house will have its own address) and the last 3 to control the unit. I have decided to test whether 5 bit will be sufficient to control devices. As some of the customers would like appliance to turn on/off only, and will have only one equipment to control. It should be enough to use the 5 bit, where the first 4 bit will serve as start and error-checking code, and the 5th bit to switch on/off the device.




Figure 4.12: 5-bit code

“1101” is set to be as “start code” and control bit is “1” to turn on, and “0” to turn off. All the coding was written in Assembly, please refer to the Appendix for more details and description of almost every line.

So, here is the testing that has been done for the coding of the Sender. To make it easier to understand the simulation part, reader should refer to the table of pins used.

Pins	Functionality
1. RBO	Serves as interrupt, and detects the zero-crossing. Has a built-in function to be triggered by raising and falling edge of the input signal.
2. RB5	The pin where the “triggering device” will be connected. To send “turn ON” command.
3. RB6	The pin where the “triggering device” will be connected. To send “turn OFF” command.
4. RC2	The output from the Sender part.
5. RC0	It is on the Receiver part. The input from the Signal Extractor.

Table 1: PIC pins used in simulation and coding




Figure 4.13: Sending “11011”-switch On command

As you can observe from the Figure 4.13, there is PB5 which is “On”, meaning that “Switch On” command is sent. PB0 is turned on and off manually, as to simulate the zero-crossings of the powerline signal. And PC2 is output of the Sender, which is triggered by zero-crossing to send a “11011”-switch On command.

In the same way, but with PB5=Off and PB6=On, the switch Off (“11010”) command is sent to the Receiver.




Figure 4.14: Sending “11010”-switch Off command

On the Receiver part, the same pins mentioned above are used. PB0 and PC0 are inputs from the powerline and Signal Extractor circuit respectively. Both PB0 and PC0 are turned on/off manually, but with respect to commands (“11011” and “11010”). And from below snapshots it can be observed that PB4 (PIC pin which supposed to control the TRIAC or Relay) is triggered by commands and functions properly.




Figure 4.15: Sending “ON” signal. (11011)

And on the Figure 4.16, there are “11010” and “11011” bits sent to switch “OFF” and “ON” the device.




Figure 4.16: Sending “OFF” and “ON” signals. (11010 and 11011)

CHAPTER 5

CONCLUSION and RECOMMENDATION

5.1 Conclusion

Development of the X-10 based Outdoor Light Automation requires a deep knowledge and expertise in analog components, and circuit analyses. Due to the author's lack of knowledge in electrical area, the mains coupling could not be completed as it also required the electrically isolated lab to test the circuit. Thus the mains coupling is left for future enhancements of the system.

Nevertheless, the development and testing stages for all 4 out of 5 modules is completed. And the sending and receiving of 5 bit messages using 16F877 PIC is successfully simulated.

The X-10 based Outdoor Light Automation System will bring the following benefits:

- Fully-automated - the lights will be triggered by the relevant input device(for this project it is photodiode)
- Multi-purpose- we can plug into the system's socket any appliance in order to automate it.
- Portable-we can move and place the system's receiver and sender anywhere we want.
- Reprogrammable PIC- we can reprogram the PIC to change the functionality.

But I believe with an effort, any challenge can be passed, and any aim can be reached, as long as we are properly stuck to the true path.

5.2 Recommendation

I would like to recommend adding the human control to the sender module. It can be done using the infrared, or even on the module itself, by adding a LCD and some control buttons like switch on and off, dimming, numbers from 1-10 to input the

address of the required object etc. So by adding human control, we can give addresses to the receiver modules, and will be able to control up to 256 appliances.

As was mentioned before, after we have built the sender and receiver modules, we can automatize many households items. It is based on our creativity and needs, to decide where and how to apply this powerful X10 communication protocol.

REFERENCES

- [1] Dave Rye, 2004, "X-10 Technical Note", X-10 Inc., USA.
- [2] Jon Burroughs, 2002, "AN236-X-10 Home Automation Using the PIC16F877A", Microchip Technology Inc., USA
- [3] Shabsi Walfish, Omar Badoolah, 2004,"X10 Receiver Project", Cooper University, USA
- [4] "TDS1000 Oscilloscope User Manual", 2004, Tektronix Inc., USA.
- [5] Robert C. Elsenpeter, 2005, "Build Your Own Smart Home", Prentice Hall, USA
- [6] Donal Scouten, 2004, <www.x10-mentor.com>.
- [7] Mike Kuniavsky, 2007,
<http://www.orangecone.com/archives/2007/01/we_need_an_appl.html>
- [8] Smarthome Store, 2004,
<http://www.smarthome.com/about_X10_Compatible.html>
- [9] BrunoG, 2006, < <http://www.micro-examples.com>>
- [10] V. Chunduru, *Student Member, IEEE*, and N. Subramanian, *Member, IEEE*, 2007, "Effects of Power Lines on Performance of Home Control System", University of Texas at Tyler, USA
- [11] A.M.Cole, B.Q.Tran, 2002, "Home Automation to Promote Independent Living in elderly populations", HomeCare & Telerehabilitation Center, The Catholic University of America, Washington, DC.
- [12] Microchip Technology Inc., 2001, "PIC16F87x Data sheet".
- [13] Murray Gunn, 2000, "Communications Over Power Lines", University of New South Wales-IEEE, Australia.
- [14] "Microelectronics", McGraw-Hill, 1988.


[15] Kevin Wade Ackerman, 2005, "Timed Power Line Data Communication",
Thesis, Department of Electrical Engineering, University of Saskatchewan, Canada.

[16] Andrew Holme, 2004, "Wireless Thermostat.",

<<http://www.holmea.demon.co.uk/Thermostat/Stat.htm>>


APPENDICES

Appendix A: Flow Chart of the System




Note: Photo sensor will be implemented upon successful completion of the main modules.


APPENDIX B: Overall System Block Diagram




Appendix C: Full circuit for the Sender




Appendix D: Full circuit of the Receiver




Appendix E: Circuit of the Dual-Polarity Power Supply




Appendix F: Signal Extractor Circuit



Appendix G: Signal Generator and Zero-Crossing Detector Circuits.



Signal Generator Circuit



Zero-Crossing Detector Circuit

Appendix H: Zero-Crossing Detector Coding

```

PROCESSOR 16f877
#include "P16F877.INC"

__CONFIG _CP_OFF & _WDT_OFF & _HS_OSC

ORG 0X00
goto Main
org 0x04
goto interrupt_occured

BCF STATUS, RP1 ;Select bank 1
BSF STATUS, RP0
bcf OPTION_REG, INTEDG ;Interrupt on falling edge

MOVLW 0X01
MOVWF TRISB ;Set Port B0 as Input
MOVLW 0X00
MOVWF TRISC ;Set Port C as Output,for LED's

check BCF STATUS, RP1 ;Select bank 1
BCF STATUS, RP0
btfs INTCON, INTF ;check the RB0/INT flag
goto interrupt_occured
goto check

interrupt_occured BCF STATUS, RP1 ;Select bank0
BCF STATUS, RP0
MOVLW 0X01
MOVWF PORTC ; Light the RED LED
goto default

default BCF STATUS, RP1 ;Select bank 1
BSF STATUS, RP0
bcf INTCON,INTF ;make RB0/INT flag=0->interrupt didn't occur
BCF STATUS, RP1 ; Select bank0
BCF STATUS, RP0
MOVLW 0X00
MOVWF PORTC ;all are OFF
goto toggle

toggle BCF STATUS, RP1 ;Select bank 1
BSF STATUS, RP0
btfs OPTION_REG,INTEDG ;toggle bit, if falling, become rising and vice-verse.
goto tozero
goto toone

tozero bcf OPTION_REG,INTEDG
goto check

toone bsf OPTION_REG,INTEDG ;Interrupt on rising edge
goto check

END

```

Appendix I: Code to Send 5bit On/Off commands.

```

PROCESSOR 16f877
#include "P16F877.INC"
__CONFIG_CP_OFF & _WDT_OFF & _HS_OSC

ORG 0X00
goto Main
org 0x04
goto check_On_button

Main BCF STATUS, RP1 ;Select bank 1
     BSF STATUS, RP0

     MOVLW 0X01
     MOVWF TRISC ;Set Port C0 as Input
     MOVLW 0X03
     MOVWF TRISB ;Set Port B as output,B0 and B1 as input

     movlw 0x00
     movwf OPTION_REG ;interrupt on falling edge

check_zero_crossing BCF STATUS, RP1 ;Select bank 0
                   BCF STATUS, RP0

                   btfsc INTCON, INTF ;check the RB0/INT flag
                   goto check_bit_1
                   goto check_zero_crossing

check_bit_1 BCF STATUS, RP1 ;Select bank 0
            BCF STATUS, RP0

            btfsc PORTC,0 ;check for signal
            goto check_bit_2
            goto check_zero_crossing
;*****
check_bit_2 BCF STATUS, RP1 ;Select bank 0
            BCF STATUS, RP0
            btfsc INTCON, INTF ;check the RB0/INT flag
            goto check_bit_2a
            goto check_bit_2

check_bit_2a BCF STATUS, RP1 ;Select bank 0
             BCF STATUS, RP0
             btfsc PORTC,0 ;check for signal
             goto check_bit_3
             goto check_zero_crossing
;*****
check_bit_3 BCF STATUS, RP1 ;Select bank 0
            BCF STATUS, RP0
            btfsc INTCON, INTF ;check the RB0/INT flag
            goto check_bit_3a
            goto check_bit_3

check_bit_3a BCF STATUS, RP1 ;Select bank 0
             BCF STATUS, RP0
             btfsc PORTC,0 ;check for signal
             goto check_zero_crossing
             goto check_bit_4 ;3rd bit supposed to be 0-
error checking bit!

```



```

check_bit_4          BCF  STATUS, RP1      ;Select bank 0
                    BCF  STATUS, RP0

                    btfsc INTCON, INTF    ;check the RB0/INT flag
                    goto  check_bit_4a
                    goto  check_bit_4

check_bit_4a        BCF  STATUS, RP1      ;Select bank 0
                    BCF  STATUS, RP0

                    btfsc PORTC,0         ;check for signal
                    goto  check_bit_5
                    goto  check_zero_crossing

;*****
check_bit_5          BCF  STATUS, RP1      ;Select bank 0
                    BCF  STATUS, RP0

                    btfsc INTCON, INTF    ;check the RB0/INT flag
                    goto  check_bit_5
                    goto  check_bit_5a

check_bit_5a        BCF  STATUS, RP1      ;Select bank 0
                    BCF  STATUS, RP0

                    btfsc PORTC,0         ;check for signal
                    goto  ON
                    goto  OFF

ON                   movlw 0x10
                    movwf PORTB          ;switch On the Device
                    goto  check_zero_crossing

OFF                  movlw 0x00
                    movwf PORTB
                    goto  check_zero_crossing

                    END

```

Appendix J: Code to Receive 5bit On/Off commands.

```

PROCESSOR 16f877
#include "P16F877.INC"
_CONFIG_CP_OFF & _WDT_OFF & _HS_OSC

ORG 0X00
goto Main
org 0x04
goto check_bit_1

Main  BCF  STATUS, RP1      ;Select bank 1
      BSF  STATUS, RP0

      MOVLW 0X01
      MOVWF TRISC        ;Set Port C0 as Input
      MOVLW 0X03
      MOVWF TRISB        ;Set Port B as output,B0 and B1 as input

      movlw 0x00
      movwf OPTION_REG   ;interrupt on falling edge
      BCF  STATUS, RP1   ;Select bank 0
      BCF  STATUS, RP0
      MOVLW 0x03
      movwf PORTB

check_zero_crossing      BCF  STATUS, RP1      ;Select bank 1
                        BSF  STATUS, RP0

                        bcf  INTCON,INTF      ;make RB0/INT flag=0->interrupt didnt occur

toggle_1  BCF  STATUS, RP1      ;Select bank 1
          BSF  STATUS, RP0

          btfs  OPTION_REG,INTEDG  ;toggle the bit, if was falling, become rising &
          ;viceverse.
          goto  tozero_1
          goto  toone_1

tozero_1  bcf  OPTION_REG,INTEDG
          goto  continue_1
toone_1  bsf  OPTION_REG,INTEDG  ;Interrupt on rising edge
          goto  continue_1
continue_1 BCF  STATUS, RP1      ;Select bank 0
          BCF  STATUS, RP0
          BSF  PORTB,7

          btfs  INTCON, INTF      ;check the RB0/INT flag
          goto  check_bit_1
          goto  continue_1

check_bit_1 BCF  STATUS, RP1      ;Select bank 0
           BCF  STATUS, RP0

           bcf  PORTB,7
           btfs  PORTC,0          ;check for signal
           goto  check_bit_2
           goto  check_zero_crossing

```

```

check_bit_2    bsf    PORTB,6
               BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
               bcf    INTCON,INTF          ;make RB0/INT flag=0->interrupt didnt occur

toggle_2       BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0

               btfsc  OPTION_REG,INTEDG    ;toggle the bit, if it was falling, become rising
               ;and vice-verse.

               goto   tozero_2
               goto   toone_2

tozero_2       bcf    OPTION_REG,INTEDG
               goto   continue_2

toone_2        bsf    OPTION_REG,INTEDG    ;Interrupt on rising edge
               goto   continue_2

continue_2     BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0

               btfsc  INTCON, INTF         ;check the RB0/INT flag
               goto   check_bit_2a
               goto   continue_2

check_bit_2a   BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               btfsc  PORTC,0              ;check for signal
               goto   check_bit_3
               goto   check_zero_crossing

;*****
check_bit_3    bcf    PORTB,6
               BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
               bcf    INTCON,INTF          ;make RB0/INT flag=0->interrupt didnt occur

toggle_3       BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
               btfsc  OPTION_REG,INTEDG    ;toggle the bit, if it was falling, become rising
and vice-verse.
               goto   tozero_3
               goto   toone_3

tozero_3       bcf    OPTION_REG,INTEDG
               goto   continue_3

toone_3        bsf    OPTION_REG,INTEDG    ;Interrupt on rising edge
               goto   continue_3

continue_3     BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               btfsc  INTCON, INTF         ;check the RB0/INT flag
               goto   check_bit_3a
               goto   continue_3

check_bit_3a   BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               btfsc  PORTC,0              ;check for signal
               goto   check_zero_crossing
               goto   check_bit_4          ;3rd bit supposed to be 0-error checking bit!

```

```

check_bit_4    bsf    PORTB,6
               BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
toggle_4       bcf    INTCON,INTF          ;make RB0/INT flag=0->interrupt didnt occur
               BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
               btfsc  OPTION_REG,INTEDG    ;toggle the bit, if it was falling, become rising
and vice-verse.
               goto   tozero_4
               goto   toone_4
tozero_4       bcf    OPTION_REG,INTEDG
               goto   continue_4
toone_4        bsf    OPTION_REG,INTEDG    ;Interrupt on rising edge
               goto   continue_4
continue_4     BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               btfsc  INTCON, INTF         ;check the RB0/INT flag
               goto   check_bit_4a
               goto   continue_4
check_bit_4a   BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               btfsc  PORTC,0              ;check for signal
               goto   check_bit_5
               goto   check_zero_crossing
;*****
check_bit_5    bcf    PORTB,6
               BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
toggle_5       bcf    INTCON,INTF          ;make RB0/INT flag=0->interrupt didnt occur
               BCF    STATUS, RP1           ;Select bank 1
               BSF    STATUS, RP0
               btfsc  OPTION_REG,INTEDG    ;toggle the bit, if it was falling, become rising
and vice-verse.
               goto   tozero_5
               goto   toone_5
tozero_5       bcf    OPTION_REG,INTEDG
               goto   continue_5
toone_5        bsf    OPTION_REG,INTEDG    ;Interrupt on rising edge
               goto   continue_5
continue_5     BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               btfsc  INTCON, INTF         ;check the RB0/INT flag
               goto   check_bit_5a
               goto   continue_5
check_bit_5a   BCF    STATUS, RP1           ;Select bank 0
               BCF    STATUS, RP0
               bsf    PORTB,6
               btfsc  PORTC,0              ;check for signal
               goto   ON
               goto   OFF
ON              movlw  0x10
               movwf  PORTB                ;switch On the Device
               goto   check_zero_crossing
OFF             movlw  0x00
               movwf  PORTB
               goto   check_zero_crossing
               END

```

Appendix K: Gantt Chart

